





TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Ninety degree
Mounting Hole Diameter	10,4 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2
Open Cavities	1
Cavity	T-23A
Port Size	1 1/4" BSPP
Model Weight	1.39 kg.

NOTES *Important:* Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
PCY, /10, /11	Ports 1 & 2: 1 1/4" BSPP; Ports 3 & 4: 1/4" BSPP;

CONFIGURATION OPTIONS
Model Code Example: PCYArray


MODIFIER
6061-T651 Aluminum, Buna-N
/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/S 65-45-12 Ductile Iron, Buna-N, Dewatering Oil
/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
/S4 65-45-12 Ductile Iron, Buna-N, Chem. Black
/S5 65-45-12 Ductile Iron, Buna-N, Electroless Nickel

MANIFOLD FACES


FACE GRID

1	2	3	4
5	6	7	8
9	10	11	12


Face 2




Face 5



Face 6



Face 7



Face 10

