

JP-480 Explosion-proof electric universal motor


230 Volt, 50/60 Hz, 825 Watt, IP 55, II 2G Ex db IIC T6 Gb

Description

- The drive JP-480 is a compactly built, robust explosion-proof universal motor that is built and approved in accordance with the latest explosion protection guidelines (ATEX 2014/34/EC) and IECEx. The collector motor is explosion-proof according to II 2G Ex db IIC T6 Gb and has an EC-type examination certificate BUREAU VERITAS 17 ATEX 1 088 X and IECEx EPS 17.0045 X. The electric motor Ex-JP-480 offers in addition to the air operated motors maximum protection when pumping flammable media or for use in hazardous environments. At such applications separate authorizations for the drive motor and the pump tube acc. directives ATEX 2014/34/EC are required.
- The handy and powerful device (6,5 kg) can be used as a drive for the ATEX certified sealless pump tubes made of Stainless steel (Ø 41 mm), the mixing pump tubes of Stainless steel, the pump tubes of Stainless steel with mechanical seal or complete drum emptying function and the eccentric screw pump tubes series JP-700 SR PTFE ATEX. In this combination the

drive is suitable for many thin liquid to viscous, neutral, lightly aggressive and easily flammable media with a flash point below 55 °C. Its sophisticated, technically clear structure ensures an efficient and safe use when transferring the wide range of media.

- The motor is characterized in addition to its robustness by its elegant design and ease of use. The non-stationarily and stationarily usable drive is particularly suitable for intermittent operation. As externally ventilated motor, it has an optimal air cooling, low noise and ensures high operational safety and long lifetime.
- The standard in the on/off switch integrated low voltage release is intended to prevent an uncontrolled start of the drum pump motor after a power failure or voltage drop. Thus guarantees maximum safety.
- The maximum density of the media is for the JP-480 universal motor 1,9, the maximum viscosity 1000 mPas.



Electric universal motor JP-480

230 Volt, 50/60 Hz, 825 Watt, protection class II 2G Ex db IIC T6 Gb, IP 55, with integrated low voltage release, 5 m cable without plug.

Optional with Ex-plug.

Operating data JP-480

Flow rate (with hose and oval gear meter):	up to 112 l/min (Rotor)*
	up to 83 l/min (Impeller)*
Head:	up to 16 m (Rotor)*
	up to 37 m (Impeller)*
Viscosity:	up to 1.000 mPas*
Density:	up to 1,9*

* Data obtained with a 1" pipe are indicated in the performance curve.

* All specified values are real measured maximum values. Test media water 20 °C, pressure pipe 1", oval gear meter 1", measured values: ± 5%



JP-480	Version	Voltage	Order No.
	without LVR	230 V 1 ~, 50/60 Hz, 825 W	1480 2300
		115 V 1 ~, 60 Hz, 825 W	1480 1150
	with LVR	230 V 1 ~, 50/60 Hz, 825 W	1480 2301
		115 V 1 ~, 60 Hz, 825 W	1480 1151

LVR: Low voltage release