

VP1 – New product designation

Ex	VP1	130	R	A	-	Z	0	-	T	-	000	-	350	/	25	-	LS
Frame Size																	
Code	Displacement																
45	45																
60	60																
75	75																
95	95																
110	110																
130	130																
Frame Size																	
Code	Rotation																
R	Right																
L	Left																
Frame Size		45	60	75	95	110	130										
Code	Suct. port																
G	BSP Thread	S	S	S	O	O	O										
A	No Thread	-	-	-	S	S	S										
Frame Size		45	60	75	95	110	130										
Code	Interface																
Z	ISO flange & shaft. G1 thread in press. Port	S	S	S	S	S	S										
C	SAE C-C flange & shaft. UN thread in press. Port	-	-	-	O	O	O										
B	*SAE B-B flange & shaft. UN thread in press. port	-	-	-	O	-	-										
* 210 bar pressure cut-off limit																	
Frame Size		45	60	75	95	110	130										
Code	Housing																
P	Through shaft	S	S	S	O	O	O										
0	Single pump	-	-	-	S	S	S										
Paint																	
Code	Paint																
T	Standard Black																
0	No Paint																

Frame Size	45	60	75	95	110	130
Code	Regulator					
LS	Std. LS	S	S	S	S	S
E1	EPC1 *	O	O	O	O	O
E2	EPC2 **	O	O	O	O	O

* 24V, Normally Open, Deutsch contact
** 24V, Normally Closed, Deutsch contact

(S) = Standard (O) = Option (-) = Not Available

* Customer specific demands, please contact Parker Hannifin