


Form B

BSP-Außengewinde mit 60°-Konus
 NPT-Innengewinde

BSP - Male with 60°-Cone
 NPT - Female



Druck Pressure	Gewinde Thread		Ca. Maße Approx. Dimensions						Form Form	Bemerkungen Notes	Bestellzeichen Order-Code
PN	G = BSP	G1 = NPT	L	L1	L2	D	SW				
400	1/8"-28	1/8"-27	25,0	8,0	11,5	4,0	14	B			1050518-02-02
400	1/8"-28	1/4"-18	31,0	8,0	16,5	4,0	19	B			1050518-02-04
400	1/4"-19	1/8"-27	32,0	12,0	11,5	6,0	19	B			1050518-04-02
400	1/4"-19	1/4"-18	32,0	12,0	16,5	6,0	19	B			1050518-04-04
400	1/4"-19	3/8"-18	31,0	10,0	15,5	7,0	24	B			1050518-04-06
400	1/4"-19	1/2"-14	38,0	10,0	22,5	7,0	27	B			1050518-04-08
400	3/8"-19	1/4"-18	36,0	12,0	17,5	9,0	22	B			1050518-06-04
400	3/8"-19	3/8"-18	36,0	12,0	17,5	9,0	24	B			1050518-06-06
400	3/8"-19	1/2"-14	37,0	12,0	20,0	9,0	27	B			1050518-06-08
400	1/2"-14	1/2"-14	39,0	14,0	20,0	12,0	27	B			1050518-08-08
400	1/2"-14	3/4"-14	46,0	14,0	22,0	13,0	36	B			1050518-08-12
400	3/4"-14	1/2"-14	44,0	16,0	23,0	18,0	32	A			1050518-12-08
400	3/4"-14	3/4"-14	48,0	16,0	22,0	18,0	36	B			1050518-12-12
400	3/4"-14	1"-11,5	51,0	16,0	28,0	18,0	41	B			1050518-12-16
400	1"-11	1"-11,5	49,5	18,0	25,0	22,0	41	B			1050518-16-16
400	1"-11	1 1/4"-11,5	50,5	18,0	27,0	22,0	50	B			1050518-16-20
200	1 1/4"-11	1 1/4"-11,5	58,0	20,0	27,0	25,0	50	B			1050518-20-20
200	1 1/2"-11	1 1/2"-11,5	62,0	22,0	28,0	37,0	55	B			1050518-24-24
100	2"-11	2"-11,5	64,0	23,0	28,5	43,0	70	B			1050518-32-32