


BSP - Zylindrisch - Männlich mit 60°-Konus
BSP - Kegelig - Männlich


BSP - Male with 60°-Cone
BSP - Taper - Male



Druck Pressure	Gewinde Thread	Ca. Maße Approx. Dimensions	Bemerkungen Notes				Bestellzeichen Order-Code
PN	G = BSP zyl. G1 = keg.	L L1 D SW					
400	1/8"-28	1/8"-28	20,0	20,0	4,0	12	1350500-02
400	1/4"-19	1/4"-19	24,5	26,0	6,0	14	1350500-04
400	3/8"-19	3/8"-19	25,5	25,5	8,0	17	1350500-06
400	1/2"-14	1/2"-14	29,5	35,0	11,0	19	1350500-08
400	3/4"-14	3/4"-14	37,0	37,0	16,0	27	1350500-12
400	1"-11	1"-11	43,0	43,0	22,0	36	1350500-16
200	1 1/4"-11	1 1/4"-11	51,0	51,0	28,5	41	1350500-20
200	1 1/2"-11	1 1/2"-11	59,0	63,0	33,5	50	1350500-24
100	2"-11	2"-11	77,5	77,5	45,0	65	1350500-32

BSP - Zylindrisch - Männlich mit 60°-Konus
NPT - Männlich

BSP - Male with 60°-Cone
NPT - Male



Druck Pressure	Gewinde Thread	Ca. Maße Approx. Dimensions	Bemerkungen Notes				Bestellzeichen Order-Code
PN	G = BSP zyl. G1 = NPT	L L1 D SW					
400	1/8"-28	1/8"-27,0	20,0	20,0	4,0	12	1350522-02
400	1/4"-19	1/4"-18,0	24,5	26,0	6,0	14	1350522-04
400	3/8"-19	3/8"-18,0	25,5	25,5	8,0	17	1350522-06
400	1/2"-14	1/2"-14,0	29,5	35,0	11,0	19	1350522-08
400	3/4"-14	3/4"-14,0	37,0	37,0	16,0	27	1350522-12
400	1"-11	1"-11,5	43,0	43,0	22,0	36	1350522-16
200	1 1/4"-11	1 1/4"-11,5	51,0	51,0	28,5	41	1350522-20
200	1 1/2"-11	1 1/2"-11,5	59,0	63,0	33,5	50	1350522-24
100	2"-11	2"-11,5	77,5	77,5	45,0	65	1350522-32