


Form A

NPT-Außengewinde mit 60°-Konus
BSP-Innengewinde

NPT - Male with 60°-Cone
BSP - Female




Druck Pressure	Gewinde Thread		Ca. Maße Approx. Dimensions					Form Form	Bemerkungen Notes	Bestellzeichen Order-Code
PN	G = NPT	G1 = BSP	L	L1	L2	D	SW			
400	1/2"-14	1/8"-28	26,0	20,0	11,0	8,5	22	A		1050517-08-02
400	1/2"-14	1/4"-19	27,0	20,0	17,0	13,0	24	A		1050517-08-04
400	3/4"-14	3/8"-19	28,0	20,0	17,0	15,0	27	A		1050517-12-06
400	1"-11,5	1/2"-14	34,0	25,0	20,0	19,0	36	A		1050517-16-08
200	1 1/4"-11,5	3/4"-14	40,0	25,5	22,5	24,2	46	A		1050517-20-12
200	1 1/4"-11,5	1"-11	40,0	25,5	25,0	30,6	46	A		1050517-20-16
200	1 1/2"-11,5	1"-11	40,0	26,0	25,0	30,6	55	A		1050517-24-16

Form B

NPT-Außengewinde mit 60°-Konus
BSP-Innengewinde

NPT - Male with 60°-Cone
BSP - Female



Druck Pressure	Gewinde Thread		Ca. Maße Approx. Dimensions						Form Form	Bemerkungen Notes	Bestellzeichen Order-Code
PN	G = NPT	G1 = BSP	L	L1	L2	D	SW				
400	1/8"-27	1/8"-28	25,0	10,0	12,0	4,0	14	B			1050517-02-02
400	1/8"-27	1/4"-19	30,0	10,0	17,0	4,0	19	B			1050517-02-04
400	1/4"-18	1/8"-28	30,0	15,0	12,0	6,0	14	B			1050517-04-02
400	1/4"-18	1/4"-19	34,0	15,0	17,0	6,0	19	B			1050517-04-04
400	1/4"-18	3/8"-19	35,0	15,0	17,0	6,0	24	B			1050517-04-06
400	1/4"-18	1/2"-14	36,5	15,0	20,0	5,0	27	B			1050517-04-08
400	3/8"-18	1/4"-19	35,0	15,0	17,0	9,0	19	B			1050517-06-04
400	3/8"-18	3/8"-19	35,0	15,0	17,0	9,0	24	B			1050517-06-06
400	3/8"-18	1/2"-14	37,0	15,0	20,0	9,0	27	B			1050517-06-08
400	1/2"-14	3/8"-19	38,0	20,0	17,0	12,0	24	B			1050517-08-06
400	1/2"-14	1/2"-14	41,0	20,0	20,0	12,0	27	B			1050517-08-08
400	1/2"-14	3/4"-14	48,0	20,0	22,5	12,0	32	B			1050517-08-12
400	3/4"-14	1/2"-14	42,0	20,0	20,0	15,0	27	B			1050517-12-08
400	3/4"-14	3/4"-14	48,0	20,0	22,5	18,0	32	B			1050517-12-12
400	3/4"-14	1"-11	50,0	20,0	25,0	18,0	41	B			1050517-12-16
400	1"-11,5	3/4"-14	54,0	25,0	22,5	21,0	36	B			1050517-16-12
400	1"-11,5	1"-11	57,0	25,0	25,0	21,0	41	B			1050517-16-16
200	1"-11,5	1 1/4"-11	57,0	25,0	27,0	21,0	55	B			1050517-16-20
200	1 1/4"-11,5	1 1/4"-11	57,5	25,5	27,0	30,0	55	B			1050517-20-20
200	1 1/4"-11,5	1 1/2"-11	62,5	25,5	27,5	30,0	55	B			1050517-20-24
200	1 1/2"-11,5	1 1/4"-11	56,0	26,0	27,0	36,0	55	B			1050517-24-20
200	1 1/2"-11,5	1 1/2"-11	63,0	26,0	27,5	36,0	55	B			1050517-24-24
100	1 1/2"-11,5	2"-11	64,0	26,0	30,5	36,0	70	B			1050517-24-32
100	2"-11,5	2"-11	64,0	26,0	30,5	46,0	70	B			1050517-32-32