


Form A

NPT-Außengewinde mit 60°-Konus
NPT-Innengewinde

NPT - Male with 60°-Cone
NPT - Female




Druck Pressure	Gewinde Thread		Ca. Maße Approx. Dimensions				Form Form	Bemerkungen Notes	Bestellzeichen Order-Code
PN	G = NPT	G1 = NPT	L	L1	D	SW			
630	3/8"-18	1/8"-27	23,0	15,3	8,5	19	A		1050525-06-02
630	1/2"-14	1/8"-27	27,0	20,0	8,5	24	A		1050525-08-02
630	1/2"-14	1/4"-18	27,0	20,0	11,0	24	A		1050525-08-04
630	3/4"-14	1/4"-18	28,0	20,0	11,0	27	A		1050525-12-04
630	3/4"-14	3/8"-18	28,0	20,0	14,0	27	A		1050525-12-06
400	1"-11,5	3/8"-18	34,0	25,0	14,0	36	A		1050525-16-06
400	1"-11,5	1/2"-14	34,0	25,0	17,7	36	A		1050525-16-08
400	1 1/4"-11,5	3/4"-14	39,5	25,5	23,0	46	A		1050525-20-12
400	1 1/2"-11,5	3/4"-14	40,0	26,0	22,5	50	A		1050525-24-12
400	1 1/2"-11,5	1"-11,5	40,0	26,0	28,5	50	A		1050525-24-16
315	2"-11,5	1"-11,5	40,0	26,0	28,5	65	A		1050525-32-16
315	2"-11,5	1 1/4"-11,5	40,0	26,0	37,2	65	A		1050525-32-20
315	2"-11,5	1 1/2"-11,5	40,0	26,0	43,2	65	A		1050525-32-24

Form B

NPT-Außengewinde mit 60°-Konus
NPT-Innengewinde

NPT - Male with 60°-Cone
NPT - Female



Druck Pressure	Gewinde Thread		Ca. Maße Approx. Dimensions						Form Form	Bemerkungen Notes	Bestellzeichen Order-Code
PN	G = NPT	G1 = NPT	L	L1	L2	D	SW				
630	1/8"-27	1/8"-27	25,0	10,0	12,0	4,0	14	B			1050525-02-02
630	1/8"-27	1/4"-18	31,0	10,0	17,5	4,0	19	B			1050525-02-04
630	1/4"-18	1/8"-27	30,0	15,0	14,0	6,0	14	B			1050525-04-02
630	1/4"-18	1/4"-18	36,0	15,0	17,5	6,0	19	B			1050525-04-04
630	1/4"-18	3/8"-18	37,0	15,0	18,0	6,0	24	B			1050525-04-06
630	1/4"-18	1/2"-14	42,0	15,0	23,0	6,0	27	B			1050525-04-08
630	3/8"-18	1/4"-18	36,0	15,0	17,5	9,0	19	B			1050525-06-04
630	3/8"-18	3/8"-18	37,0	15,0	17,5	9,0	24	B			1050525-06-06
630	3/8"-18	1/2"-14	41,0	15,0	23,0	9,0	27	B			1050525-06-08
630	1/2"-14	3/8"-18	39,5	20,0	17,5	12,0	24	B			1050525-08-06
630	1/2"-14	1/2"-14	46,0	20,0	23,0	12,0	27	B			1050525-08-08
630	1/2"-14	3/4"-14	48,0	20,0	23,0	12,0	36	B			1050525-08-12
630	3/4"-14	1/2"-14	42,0	20,0	25,0	15,0	27	B			1050525-12-08
630	3/4"-14	3/4"-14	48,0	20,0	23,0	18,0	36	B			1050525-12-12
400	3/4"-14	1"-11,5	50,0	20,0	25,0	18,0	36	B			1050525-12-16
400	1"-11,5	3/4"-14	34,0	25,0	23,0	22,6	36	B			1050525-16-12
400	1"-11,5	1"-11,5	57,0	25,0	27,5	21,0	41	B			1050525-16-16
400	1"-11,5	1 1/4"-11,5	57,0	25,0	27,0	21,0	50	B			1050525-16-20
400	1 1/4"-11,5	1"-11,5	54,0	25,5	28,0	28,5	46	B			1050525-20-16
400	1 1/4"-11,5	1 1/4"-11,5	55,0	25,5	27,0	30,0	50	B			1050525-20-20
400	1 1/4"-11,5	1 1/2"-11,5	62,5	25,5	28,5	30,0	55	B			1050525-20-24
400	1 1/2"-11,5	1 1/4"-11,5	55,0	26,0	27,0	36,0	50	B			1050525-24-20
400	1 1/2"-11,5	1 1/2"-11,5	63,0	26,0	28,5	36,0	55	B			1050525-24-24
315	1 1/2"-11,5	2"-11,5	64,0	26,0	28,5	36,0	70	B			1050525-24-32