

MV - MANOMETER - VERSCHRAUBUNGEN

MV - PRESSURE - GAUGE - COUPLINGS



EDELSTAHL / STAINLESS STEEL
VERBINDUNGSTECHNIK
FLUID CONNECTORS

Manometer-Verschraubungen


Mit Dichtkantenring - DKRi

Innengewinde: Whitworth-Rohrgewinde - Zylindrisch

Gauge Couplings

With Metal Sealing Ring - DKRi

Internal Thread: BSP - Female - Parallel



Reihe / Series L

Druck Pressure	Rohr A.D. Tube O.D.	Gewinde Thread	Ca. Maße Approx. Dimensions					Bestellzeichen Order-Code	
PN	D1	G	H	L1	L2	i	SW1	SW3	
315	6	G 1/4"	4,5	37,0	7,5	14,5	19	14	MV-L-06-G 1/4"
315	6	G 1/2"	5,0	46,0	9,0	20,0	27	14	MV-L-06-G 1/2"
315	8	G 1/4"	4,5	37,0	7,5	14,5	19	17	MV-L-08-G 1/4"
315	8	G 1/2"	5,0	46,0	9,0	20,0	27	17	MV-L-08-G 1/2"
315	10	G 1/4"	4,5	38,0	8,5	14,5	19	19	MV-L-10-G 1/4"
315	10	G 1/2"	5,0	47,0	9,5	20,0	27	19	MV-L-10-G 1/2"
315	12	G 1/4"	4,5	38,0	8,5	14,5	19	22	MV-L-12-G 1/4"
315	12	G 1/2"	5,0	48,0	10,0	20,0	27	22	MV-L-12-G 1/2"

Reihe / Series S

Druck Pressure	Rohr A.D. Tube O.D.	Gewinde Thread	Ca. Maße Approx. Dimensions					Bestellzeichen Order-Code	
PN	D1	G	H	L1	L2	i	SW1	SW3	
630	6	G 1/2"	5,0	46,0	11,0	20,0	27	17	MV-S-06-G 1/2"
630	8	G 1/4"	4,5	40,0	9,5	14,5	19	19	MV-S-08-G 1/4"
630	8	G 1/2"	5,0	46,0	11,0	20,0	27	19	MV-S-08-G 1/2"
630	10	G 1/4"	4,5	40,5	9,0	14,5	19	22	MV-S-10-G 1/4"
630	10	G 1/2"	5,0	47,0	10,5	20,0	27	22	MV-S-10-G 1/2"
630	12	G 1/4"	4,5	41,0	8,0	14,5	22	24	MV-S-12-G 1/4"
630	12	G 1/2"	5,0	47,0	10,5	20,0	27	24	MV-S-12-G 1/2"
630	14	G 1/2"	5,0	49,5	12,0	20,0	27	27	MV-S-14-G 1/2"