## Mosmatic swivels DGS / DGV /DGK

Housing stainless steel / nickel-plated brass. Axle stainless steel. DN 6. Rust-proof and maintenance-free. Field of application: Swivels applicable to high pressure spray guns and hose connections, ceiling booms in self-service car wash. Max. 275 bar / 30 r.p.m. / 120 °C

**DGS.** Double ball bearing system

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 300 01 | 1/4" F | 1/4" M | 59 mm |
| 108 300 02 | 1/4" F | 1/4" F | 62 mm |
| 108 300 03 | 1/4" F | 3/8" M | 60 mm |
| 108 300 04 | 1/4" F | 3/8" F | 63 mm |
| 108 300 05 | 1/4" F | M14 M | 57 mm |
| 108 300 06 | 1/4" F | M16 M | 57 mm |
| 108 300 07 | 1/4" F | M18 M | 57 mm |
| 108 300 09 | 1/4" F | M22 M | 61 mm |
| 108 301 03 | 3/8" F | 3/8" M | 60 mm |
| 108 301 04 | 3/8" F | 3/8" F | 63 mm |
| 108 301 07 | 3/8" F | M18 M | 57 mm |
| 108 301 09 | 3/8" F | M22 M | 61 mm |

**DGV.** Single ball bearing system

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 325 11 | 1/4" M | 1/4" M | 60 mm |
| 108 325 12 | 1/4" M | 1/4" F | 63 mm |
| 108 325 13 | 1/4" M | 3/8" M | 61 mm |
| 108 325 18 | 1/4" M | M21 M | 62 mm |
| 108 325 21 | 3/8" M | 1/4" M | 60 mm |
| 108 325 24 | 3/8" M | 3/8" F | 61 mm |
| 108 325 32 | 3/8" M | 1/4" F | 63 mm |
| 108 325 33 | 3/8" M | 3/8" M | 61 mm |
| 108 325 34 | 3/8" M | 3/8" F | 63 mm |
| 108 325 37 | 3/8" M | M18 M | 58 mm |
| 108 325 39 | 3/8" M | M22 M | 62 mm |
| 108 325 82 | 1/4" F | 1/4" F | 67 mm |
| 108 325 87 | 1/4" F | M18 M | 62 mm |

**DGK.** Single ball bearing system

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 320 31 | 1/4" M | DN 06 | 58 mm |
| 108 320 33 | 1/4" F | DN 06 | 62 mm |
| 108 321 32 | 3/8" M | DN 08 | 66 mm |

## Mosmatic swivels DGVI

Stainless steel. DN 6. Rust-proof and maintenance-free. Field of application: Swivels applicable to high pressure spray guns and hose connections. Max. 500 bar / 30 r.p.m. / 120 °C

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 327 02 | 1/4" M* | 1/4" F | 54 |
| 108 327 24 | 3/8" M* | 3/8" F | 56 |
| 108 327 34 | 3/8" M | 3/8" F | 64 |
| 108 328 14 | 1/2" M | 1/2" F | 75 |

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 327 81 | 1/4" F | 1/4" M | 64 |
| 108 327 83 | 1/4" F | 3/8" M | 65 |

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 327 82 | 1/4" F | 1/4" F | 66 |
| 108 327 84 | 1/4" F | 3/8" F | 68 |

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 327 87 | 1/4" F | M18 M | 62 |
| 108 327 88 | 1/4" F | M21 M | 66 |
| 108 327 89 | 1/4" F | M22 M | 66 |

## Mosmatic swivels DGE / DGEI

Maintenance-free. Field of application: especially designed for high flow rates and low revolutions per minute as for example at automatic car wash plants. Max. 30 r.p.m. / 120 °C. DN 13 for 1/2". DN 25 for 1"

**DGE 90°.** Housing nickel-plated brass. Single ball bearing system. Rust-proof. Max. 275 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 348 23 | 1/2" F | 1/2" M | 99 |

Max. 200 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 348 25 | 1" F | 1" M | 123 |

**DGE.** Housing nickel-plated brass. Single ball bearing system. Rust-proof. Max. 275 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 348 03 | 1/2" F | 1/2" M | 80 |

Max. 200 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 348 05 | 1" F | 1" M | 90 |

**DGEI.** Housing stainless steel. Triple ball bearing system. Max. 350 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 347 03 | 1/2" F | 1/2" M | 80 |

Max. 200 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 347 05 | 1" F | 1" M | 95 |

**DGEI 90°.** Housing stainless steel. Triple ball bearing system. Max. 350 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 347 23 | 1/2" F | 1/2" M | 99 |

Max. 200 bar

| R+M Nr. | ⇦ | ⇨ | ↔ |
|---|---|---|---|
| 108 347 25 | 1" F | 1" M | 123 |

* conical

**Symbols** ⇦ inlet ⇨ outlet ↕ height ↔ length mm VPE packing unit