

ADJUSTABLE ANGLE COUPLINGS LOW PRESSURE - ST. STEEL

P/N	Inlet	Outlet	Weight			
			gr	oz		
26.1600.00	1/4 Bsp M	1/4 Bsp F	136	4,8	10	✓
Rated Pressure		50 bar - 5 MPa		700 psi		
Rated Flow		40 l/min		10,5 USGpm		
Rated Temperature		90 °C		195 °F		
Material		Stainless steel 303				



ADJUSTABLE ANGLE COUPLINGS HIGH PRESSURE - ST. STEEL

P/N	Inlet	Outlet	Weight			
			gr	oz		
26.1700.00	1/4 Npt M	1/4 Npt F	94	3,32	10	✓
26.1700.15	1/4 Bsp M	1/4 Bsp F	94	3,32	10	✓
Rated Pressure		275 bar - 27,5 MPa		4000 psi		
Rated Flow		40 l/min		10,5 USGpm		
Rated Temperature		90 °C		195 °F		
Angle of rotation				60°		
Material		Stainless steel 303				



TD1 - DOUBLE NOZZLE HOLDER

P/N	Inlet	Outlet	Weight			
			gr	oz		
23.0000.00	1/4 Bsp F	2 × 1/4 Npt F	165	5,8	25	✓
23.0000.50	1/4 Bsp F	2 × 1/8 Npt F	174	6,14	25	✓
Rated Pressure			200 bar - 20 MPa		2900 psi	
Permissible Pressure			220 bar - 22 MPa		3200 psi	
Rated Flow			40 l/min		10,5 USGpm	
Rated Temperature			90 °C		195 °F	



TD1P - DOUBLE NOZZLE HOLDER WITH KNOB

P/N	Inlet	Outlet	Weight			
			gr	oz		
23.0015.00	1/4 Bsp F	2 × 1/4 Npt F	194	6,84	25	✓
23.0015.50	1/4 Bsp F	2 × 1/8 Npt F	200	7	25	
Rated Pressure			200 bar - 20 MPa		2900 psi	
Permissible Pressure			220 bar - 22 MPa		3200 psi	
Rated Flow			40 l/min		10,5 USGpm	
Rated Temperature			90 °C		195 °F	



TR1 - ADJUSTABLE NOZZLE HOLDER

P/N	Inlet	Outlet	Weight			
			gr	oz		
22.0000.00	1/4 Bsp F	1/4 Npt F	116	4,09	25	✓
22.0000.15	1/4 Bsp F	1/8 Npt F	122	4,3	25	✓
22.0000.05	1/4 Npt F	1/4 Npt F	115	4,06	25	✓
Rated Pressure			250 bar - 25 MPa		3650 psi	
Permissible Pressure			280 bar - 28 MPa		4050 psi	
Rated Flow			30 l/min		8 USGpm	
Rated Temperature			160 °C		320 °F	

