

Suttner high pressure quick couplings ST-3100

Couplings and plug ST-3100

Coupling : F. Stainless steel.
Max. 250 bar / 150 °C

⊙	DN
1/4"	10
3/8"	12
1/2"	12

R+M Nr.	I
203 100 466	44 mm
203 100 461	44 mm
203 100 460	44 mm

Coupling : F. Stainless steel.
Max. 250 bar / 150 °C

R+M Nr.	I
203 100 456	50 mm
203 100 455	50 mm

Coupling : M. Stainless steel.
60 °Cone. Max. 250 bar / 150 °C

R+M Nr.	I
203 100 474	50 mm
203 100 655	45 mm

Coupling : M. Stainless steel.
60 °Cone. Max. 250 bar / 150 °C

⊙	DN
1/4"	10
3/8"	12
1/2"	12

R+M Nr.	I
203 100 652	53 mm
203 100 473	55 mm
203 100 656	54 mm

Plug : F. Stainless steel.
Max. 250 bar / 150 °C

R+M Nr.	I
040 005 665	35 mm
040 005 667	41 mm
040 005 661	47 mm

Plug : M. Stainless steel. 60 °Cone.
Max. 250 bar / 150 °C

R+M Nr.	I
040 005 668	47 mm
040 005 662	47 mm

Plug : F. Hardened stainless steel.
Max. 250 bar / 150 °C

⊙	DN
1/4"	10
3/8"	12
1/2"	12

R+M Nr.	I
040 005 465	35 mm
040 005 467	41 mm
040 005 461	47 mm

Plug : M. Hardened stainless steel. 60
°Cone. Max. 250 bar / 150 °C

R+M Nr.	I
040 005 459	47 mm
040 005 462	47 mm

Plug : F. Stainless steel. For moulded
handles. Max. 250 bar / 150 °C

R+M Nr.	I
040 005 664	40 mm

Plug : F. Stainless steel + brass.
Max. 250 bar / 150 °C

⊙	DN
M22	10

R+M Nr.	I
203 100 665	56 mm

Coupling : M. Stainless steel.
Max. 250 bar / 150 °C

R+M Nr.	I
203 100 660	57 mm



O-ring large EPDM

R+M Nr.	VPE
050 000 196	1
791 552 610	100



O-ring large EPDM

R+M Nr.	VPE
050 000 664	1
791 821 01	100

Couplings "B"

Coupling : F. Stainless steel.
Max. 150 bar / 90 °C

⊙	DN
1/2"	11

R+M Nr.	I
710 247 212 000	35 mm

Plug : M. Stainless steel.
Max. 150 bar / 90 °C

R+M Nr.	I
710 247 112 100	44 mm



O-ring. 13x2

R+M Nr.	I
791 32	