

ARS250-35MPA-SST BALL-TYPE QUICK COUPLING 35MPA

P/N	Inlet	Type	Weight			
			gr	oz		
26.2005.00	3/8 Bsp M	B	101	3,56	25	 
26.2005.10	3/8 Bsp F	B1	118	4,16	25	
26.2006.51R	3/8 Bsp M	A	44	1,55	25	
26.2007.51R	3/8 Bsp F	A1	50	1,7	25	

Rated Pressure	350 bar - 35 MPa	5100 psi
Permissible Pressure	390 bar - 39 MPa	5650 psi
Rated Flow	30 l/min	8 USGpm
Rated Temperature	90 °C	195 °F
Material	Stainless steel	

Pin Ø15 mm - Internal hole Ø8,5 mm



ARS 350 -STAINLESS STEEL BALL-TYPE QUICK COUPLING 350 BAR

P/N	Inlet	Type	Mat.	Weight			
				gr	oz		
26.2045.51R	1/4 Bsp M	A	St. steel	59	2,08	25	 
26.2040.51R	1/4 Bsp F	A	St. steel	68	2,4	25	
26.2048.51R	3/8 Bsp M	A	St. steel	74	2,61	25	
26.2035.51R	3/8 Bsp F	A	St. steel	57	2,01	25	
26.2050.20	1/4 Bsp F	B	St. steel	166	5,85	25	
26.2050.25	1/4 Bsp M	B	St. steel	158	5,59	25	
26.2050.00	3/8 Bsp F	B	St. steel	158	5,57	25	

Rated Pressure	350 bar - 35 MPa	5100 psi
Permissible Pressure	390 bar - 39 MPa	5650 psi
Rated Flow	50 l/min	13,2 USGpm
Rated Temperature	90 °C	195 °F

Pin Ø19,9 mm - Internal hole Ø12 mm - Compatible with ARS220



ARS 350 P -STAINLESS STEEL BALL-TYPE QUICK COUPLING 35MPA

P/N	Inlet	Type	Mat.	Weight			
				gr	oz		
26.2055.25	1/4 Bsp M	B	St. steel	192	6,77	25	✓

Rated Pressure	350 bar - 35 MPa	5100 psi
Permissible Pressure	390 bar - 39 MPa	5650 psi
Rated Flow	50 l/min	13,2 USGpm
Rated Temperature	90 °C	195 °F
Casing colour	Black	

Pin Ø19,9 mm - Internal hole Ø12 mm

