

Foam lances

ST-74 foam lances with air injector



1/4" F. Foam lance stainless steel with air injector and stainless steel socket with nozzle 40° 150. Max. 90 °C

R+M Nr.	D	air injector	Ø	M	↔
200 074 505*	2.1 mm		0.8 kg	stainless steel	530 mm
200 074 500	2.3 mm		0.8 kg	stainless steel	530 mm

Foam Nozzle Polypropylene

Max. 45 bar / 60 °C. 75 mm




R+M Nr.	D	Ø	G	C
203 100 910	50° 200	0.42 kg	1/2" M	white



R+M Nr.	D	Ø	G	C
203 100 920	50° 200	0.43 kg	plug ST-3100	white
203 100 955	50° 200	0.43 kg	plug ST-3100	blue
203 100 965	50° 200	0.43 kg	plug ST-3100	green
203 100 975	50° 200	0.43 kg	plug ST-3100	red
203 100 985	50° 200	0.43 kg	plug ST-3100	yellow

Foam lance ST-3100




Plug ST-3100. Foam lance stainless steel 300 mm with foam nozzle 50° 200

R+M Nr.	D	ISO	M	↔
203 100 630	50° 200	-	stainless steel	300 mm



Nozzle protector ST-11



- » The nozzle protector ST-11 is suitable for nozzles 1/4" M.
- » Made out of plastics intended to come into contact with foodstuffs according to Regulation (EC) No. 1935/2004.
- » It is clamped undetachably between the nozzle and the nozzle sleeve.

R+M Nr.	C
020 001 124	white
020 001 149	blue
020 001 121	red
020 001 122	green

R+M Nr.	C
020 001 123	yellow
020 001 157	grey
020 001 158	black

* limited stock

Symbols inlet nozzle height length weight material insulation colour thread packing unit thickness mm