

Rinsing lances

Rinsing lance with insulated grip



ST-3100 connector. 280 mm rinsing lance made of stainless steel with 100 mm insulation and nozzle protection ST-11 with nozzle.

Max. 250 bar / 150 °C

R+M Nr.	D	ISO	M	
200 129 183	15° 20	100 mm	stainless steel	280 mm

Rinsing lance, bended with insulated grip



ST-3100 connector. 280 mm bended rinsing lance made of stainless steel with 100 mm insulation and nozzle protection ST-11 with nozzle.

Max. 250 bar / 150 °C

R+M Nr.	D	ISO	M	
200 129 184	15° 20	100 mm	stainless steel	280 mm

Lances with female thread



1/4" M. Lance with moulded handle Cool & Compact. Comfortable grip and ergonomic shape. Heat-proof insulation. Max. 400 bar / 150 °C

R+M Nr.		ISO		M
200 129 140	1/4" F BSP	300 mm	500 mm	stainless steel
200 129 145	1/4" F BSP	400 mm	700 mm	stainless steel
200 129 150	1/4" F BSP	400 mm	800 mm	stainless steel

R+M Nr.



1/4" M. Lance. Max. 400 bar / 150 °C

R+M Nr.			M
070 000 097	1/4" F BSP	100 mm	stainless steel
070 000 098	1/4" F BSP	150 mm	stainless steel
070 000 099	1/4" F BSP	200 mm	stainless steel
070 000 095	1/4" F BSP	250 mm	stainless steel
070 000 101	1/4" F BSP	350 mm	stainless steel

R+M Nr.

Rubber protected ball valves



Stainless steel.
Max. 60 bar / 95 °C

R+M Nr.		
500 155	1/2" F	ST-3100



Stainless steel.
Max. 60 bar / 95 °C

R+M Nr.		
500 150	1/2" F	1/2" F



Stainless steel.
Max. 60 bar / 95 °C

R+M Nr.		
500 160	1/2" F	1/2" F



ST-3100. Stainless steel.
Max. 60 bar / 95 °C

R+M Nr.		
203 100 250	1/2" F	1/2" F



ST-3100. Stainless steel.
Max. 60 bar / 95 °C

R+M Nr.		
203 100 260	1/2" F	ST-3100