


Foam lances

Spare parts ST-3100



Plug ST-3100 with foam nozzle 50° 200

R+M Nr.
502 808

Plug : 1/2" F.
Stainless steel.
Max. 250 bar / 150 °C

R+M Nr.	I
040 005 661	47 mm

1/2" M. Brass. Foam
nozzle

R+M Nr.	D
502 803 1	50° 200
626 304	65° 100

1/2" M BSP. Stainless
steel. Foam nozzle

R+M Nr.	D
500 101 3	50° 200

1/2" M NPT. Stainless
steel. Foam nozzle

R+M Nr.	D
502 803 19	50° 200



Nozzle protector

R+M Nr.
020 001 148

Spare parts nozzle head

3/8" F : 1/4" F. Nozzle
head without nozzle.
Stainless steel

R+M Nr.
200 072 491

3/8" M.
Stainless steel

R+M Nr.	D
623 401 509	40° 150

3/8" M. For lances ST-
72.1 / 72. Stainless steel.

R+M Nr.	D
120 501 204	50° 120

Splash guard

ST-29 Cool & Compact with splash guard

Lance with insulation ST-29 Cool & Compact. Pleasantly ergonomic shaped
handle. Closed surface. With splash guard, adjustable with thumbscrew.
Max. 400 bar / 80 °C

R+M Nr.	ISO	ISO	ISO	M
200 029 350	1/4" M	300 mm	900 mm	stainless steel

Chemistry Glove Solvex®

Category III -Protection Glove AlphaTec® Solvex®37-675.
Very durable nitrile glove for use with hazardous chemicals. The reversed
lozenge finish further enhances levels of grip. Cotton-flock liner to the
glove

R+M Nr.	VPE	size	size
956 067 511	1 pair	0.38	11 330 mm
956 167 511	12 pairs	0.38	11 330 mm
956 267 511	144 pairs	0.38	11 330 mm

PVC splash guard, with
thumb screw adjustable
stainless steel holder for
attachment to lances.
Max. 80 °C

R+M Nr.	Ø
200 029 351	200 mm

Spare parts

Plastic.
Stainless steel

R+M Nr.
200 010 740

2 x 1/4" F : 1/4" F. ST-58
change-over valve.
Max. 350 bar / 45 l/min

R+M Nr.
200 058 600

1/4" F : 1/4" F. S
stainless steel. Socket

R+M Nr.
040 004 100

1/4" F NPT : 3/8" F.
Stainless steel. Socket

R+M Nr.
710 101 350

Plug ST-3100. Plug with nozzle protector ST-10
and nozzle 40° 30

R+M Nr.
502 807