

AR1 - "A" NIPPLE - 2×M22 - Ø14MM - WITH KNOB

P/N	Inlet	Weight			
		gr	oz		
26.0055.00	A 2× M22	176	6,21	25	✓

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M22×1,5 M



AR1 - "A" NIPPLE M21- Ø14MM - BSP

P/N	Inlet	Weight			
		gr	oz		
26.0043.31R	1/8 Bsp F	65	2,3	10	
26.0044.31R	1/4 Bsp M	65	2,3	10	✓
26.0045.31R	1/4 Bsp F	56	1,98	10	✓
26.0046.31R	3/8 Bsp M	49	1,73	10	✓
26.0047.31R	3/8 Bsp F	65	2,3	10	✓
26.0049.31R	1/2 Bsp F	65	2,3	10	
26.0065.31R	M18 x 1,5 mm Ermeto	65	2,3	10	
26.0062.31R	M21 M	70	2,4	10	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M21×1,5 M



AR1 - "B" COUPLER M21 2 PCS. - BSP

P/N	Inlet	Weight			
		gr	oz		
26.0155.30	1/4 Bsp M	66	2,33	10	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M21×1,5 F



AR1 - "B" COUPLER M21- 3 PCS.- BSP

P/N	Inlet	Weight			
		gr	oz		
26.0270.30	1/4 Bsp M	104	3,67	25	✓
26.0270.20	1/4 Bsp F	118	4,16	25	✓
26.0270.50	3/8 Bsp M	110	3,88	25	✓
26.0270.40	3/8 Bsp F	118	4,16	25	✓

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M21×1,5 F - non-revolving pin

