

M27 x 2 - COUPLING TYPE "A+B"

P/N	Inlet	Couplings	Weight			
			gr	oz		
26.0450.00	1/4 Bsp F	A M27	84	2,96	10	
26.0460.00	1/4 Bsp F	B M27	66	2,3	10	

Rated Pressure	120 bar - 12 MPa	1750 psi
Permissible Pressure	130 bar - 13 MPa	1900 psi
Rated Flow	30 l/min	8 USGpm
Rated Temperature	60 °C	140 °F

Pin Ø14 mm



AR1 - "A" NIPPLE M22 - Ø14 MM - BSP

P/N	Inlet	Weight				
		gr	oz			
26.0029.31R	1/8 Bsp F	65	2,3	10		
26.0051.31R	1/4 Bsp M	46	1,62	25	✓	
26.0002.31R	1/4 Bsp F	65	2,3	25	✓	
26.0030.31R	3/8 Bsp M	53	1,87	25	✓	
26.0031.31R	3/8 Bsp F	68	2,4	25	✓	
26.0032.31R	1/2 Bsp M	61	2,15	25	✓	
26.0033.31R	1/2 Bsp F	80	2,82	25	✓	
26.0041.31R	A M21	65	2,3	10		
26.0005.31R	A M22	65	2,3	25	✓	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M22x1,5 M



AR41 - "A" SST. NIPPLE M22 Ø14 MM - BSP

P/N	Inlet	Weight				
		gr	oz			
26.0235.51R	3/8 Bsp F	54	1,9	5	✓	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F
Material	Stainless steel 303	

Pin Ø14 mm - M22x1,5 M



AR1 - "B" COUPLER M22 2 PCS. - BSP

P/N	Inlet	Hand nut	Weight				
			gr	oz			
26.0150.05	1/8 Bsp F	AR1 type	70	2,4	10		
26.0150.30	1/4 Bsp M	AR1 type	66	2,33	25	✓	
26.0150.20	1/4 Bsp F	AR1 type	68	2,4	25	✓	
26.9952.98	1/4 Bsp F	AR4 type	73	2,57	25	✓	
26.9954.98	1/4 Bsp F	Old type	70	2,4	25		
26.0150.40	3/8 Bsp M	AR1 type	72	2,54	25	✓	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M22x1,5 F - non-revolving pin

