



AR1 - "B" COUPLER M22 2 PCS. ROTATING PIN - BSP

P/N	Inlet	Hand nut	Weight		
			gr	oz	
26.0150.31	1/4 Bsp M	AR1 type	70	2,4	5
Rated Pressure			250 bar - 25 MPa		3650 psi
Permissible Pressure			280 bar - 28 MPa		4050 psi
Rated Flow			40 l/min		10,5 USGpm
Rated Temperature			160 °C		320 °F

Pin Ø14 mm - M22x1,5 F



AR1 - "B" COUPLER M22- 3 PCS.- BSP

P/N	Inlet	Weight		
		gr	oz	
26.0250.05	1/8 Bsp F	112	3,9	5
26.0250.30	1/4 Bsp M	104	3,67	25 ✓
26.0250.20	1/4 Bsp F	118	4,16	25 ✓
26.0250.50	3/8 Bsp M	111	3,92	25 ✓
26.0250.40	3/8 Bsp F	117	4,13	25 ✓
26.0250.70	1/2 Bsp M	124	4,37	10 ✓
26.0250.60	1/2 Bsp F	147	5,18	25 ✓
Rated Pressure		250 bar - 25 MPa		3650 psi
Permissible Pressure		280 bar - 28 MPa		4050 psi
Rated Flow		40 l/min		10,5 USGpm
Rated Temperature		160 °C		320 °F

Pin Ø14 mm - M22x1,5 F - non-revolving pin



AR1 - "B" COUPLER M22- 3 PCS. ROTATING PIN - BSP

P/N	Inlet	Weight		
		gr	oz	
26.0250.31	1/4 Bsp M	100	3,53	5 ✓
26.0250.21	1/4 Bsp F	114	4,02	5 ✓
26.0250.51	3/8 Bsp M	106	3,74	5 ✓
26.0250.41	3/8 Bsp F	114	4,02	5 ✓
26.0250.71	1/2 Bsp M	120	4,2	5
Rated Pressure		250 bar - 25 MPa		3650 psi
Permissible Pressure		280 bar - 28 MPa		4050 psi
Rated Flow		40 l/min		10,5 USGpm
Rated Temperature		160 °C		320 °F

Pin Ø14 mm - M22x1,5 F



AR41 - "B" SST. COUPLER M22- 3 PCS.- BSP

P/N	Inlet	Weight		
		gr	oz	
26.0230.40	3/8 Bsp F	125	4,41	5
Rated Pressure		250 bar - 25 MPa		3650 psi
Permissible Pressure		280 bar - 28 MPa		4050 psi
Rated Flow		40 l/min		10,5 USGpm
Rated Temperature		160 °C		320 °F
Material		Stainless steel 303		

Pin Ø14 mm - M22x1,5 F

