

AR1 - "A" NIPPLE 1/2 BSP M - Ø15MM - BSP

P/N	Inlet	Mat.	Weight		
			gr	oz	
26.0113.31R	1/4 Bsp F	Brass	52	1,83	10
Rated Pressure			250 bar - 25 MPa		3650 psi
Permissible Pressure			280 bar - 28 MPa		4050 psi
Rated Flow			40 l/min		10,5 USGpm
Rated Temperature			160 °C		320 °F

Pin Ø15 mm - 1/2 Bsp M



AR1 - "B" COUPLER 1/2 BSP F 2 PCS. -BSP

P/N	Inlet	Weight		
		gr	oz	
26.0110.20	1/4 Bsp F	64	2,26	25
Rated Pressure		250 bar - 25 MPa		3650 psi
Permissible Pressure		280 bar - 28 MPa		4050 psi
Rated Flow		40 l/min		10,5 USGpm
Rated Temperature		160 °C		320 °F

Pin Ø15 mm - 1/2 Bsp F



AR1 - "B" COUPLER 2PCS M22 - Ø15MM - BSP

P/N	Inlet	Weight		
		gr	oz	
26.9152.98	1/4 Bsp F	64	2,3	5
Rated Pressure		250 bar - 25 MPa		3650 psi
Permissible Pressure		280 bar - 28 MPa		4050 psi
Rated Flow		40 l/min		10,5 USGpm
Rated Temperature		160 °C		320 °F

Pin Ø15 mm - M22x1,5 F



AR1 - "B" COUPLER M22 - 3 PCS. - Ø15MM -BSP

P/N	Inlet	Weight		
		gr	oz	
26.0281.00	M22	110	3,88	5
26.0281.40	3/8 Bsp F	126	4,44	10
26.0281.50	3/8 Bsp M	102	3,6	10
Rated Pressure		250 bar - 25 MPa		3650 psi
Permissible Pressure		280 bar - 28 MPa		4050 psi
Rated Flow		40 l/min		10,5 USGpm
Rated Temperature		160 °C		320 °F

Pin Ø15 mm - M22x1,5 F

