

## Bayonet quick couplings

## Couplings with tail



Straight. Brass

Swivel straight.  
Brass. RotatableSuction coupling \*.  
Brass

| DN             | R+M Nr. | ⓘ  |
|----------------|---------|----|
| 10 mm (3/8")   | 720 05  | 45 |
| 13 mm (1/2")   | 720 10  | 45 |
| 16 mm (5/8")   | 720 15  | 45 |
| 19 mm (3/4")   | 720 20  | 45 |
| 25 mm (1")     | 720 30  | 51 |
| 32 mm (1.1/4") | 720 40  | 62 |
| 38 mm (1.1/2") | 720 50  | 68 |

| R+M Nr. | ⓘ  |
|---------|----|
| 720 104 | 60 |
| 720 204 | 55 |
| 720 304 | 67 |
| 720 404 | 75 |

| R+M Nr. | ⓘ  |
|---------|----|
| 724 30  | 79 |
| 724 15  | 74 |
| 724 25  | 78 |

## Couplings with male and female thread



M thread. Brass

F thread. Flat seal.  
Brass

| ⊙      |
|--------|
| 1/4"   |
| 3/8"   |
| 1/2"   |
| 3/4"   |
| 1"     |
| 1.1/4" |
| 1.1/2" |

| R+M Nr. | ⓘ  |
|---------|----|
| 723 05  | 23 |
| 723 10  | 24 |
| 723 20  | 24 |
| 723 30  | 22 |
| 723 40  | 23 |
| 723 50  | 26 |
| 723 60  | 35 |

| R+M Nr. | ⓘ  |
|---------|----|
| 722 10  | 23 |
| 722 20  | 23 |
| 722 30  | 23 |
| 722 40  | 23 |
| 723 00  | 28 |
| 723 01  | 30 |

\* Leak proof. Twist on sleeve locks in place

## Spare washer



Flat seal. For F thread

| R+M Nr. | ⊙      |
|---------|--------|
| 725 23  | 3/8"   |
| 725 24  | 1/2"   |
| 725 25  | 3/4"   |
| 725 26  | 1"     |
| 725 27  | 1.1/4" |
| 725 28  | 1.1/2" |



Gasket

| R+M Nr. |
|---------|
| 725 20  |


## Accessories

100 meshes/cm².  
Brass. Strainer  
insert. 33 mm

| R+M Nr. |
|---------|
| 725 30  |

Bayonet blank  
coupling with  
gasket. Brass

| R+M Nr. |
|---------|
| 725 10  |

3-way distributor  
3/4" F : 3/4" M :  
3/4" M. Brass

| R+M Nr. |
|---------|
| 725 05  |

3-way bayonet  
coupling.  
Brass

| R+M Nr. |
|---------|
| 725 00  |

## Low pressure quick coupling ST-45

ST-45.  
Nickel-plated brass.  
Quick Coupling :  
3/4" F.  
25 bar / 90 °C

| R+M Nr.     |
|-------------|
| 200 045 210 |

ST-45.  
Nickel-plated brass.  
Quick Coupling :  
1" F.  
25 bar / 90 °C

| R+M Nr.     |
|-------------|
| 200 045 230 |

ST-45.  
Nickel-plated brass.  
Plug nipple with  
hose barb  
13-19 mm.  
25 bar / 90 °C

| R+M Nr.     |
|-------------|
| 010 000 455 |

ST-45.  
Nickel-plated brass.  
Plug nipple with  
hose barb  
19-25 mm.  
25 bar / 90 °C

| R+M Nr.     |
|-------------|
| 010 000 456 |

KTW approved bayonet quick couplings are available on request!

Symbols ⊙ thread ⓘ height DN nominal diameter ∅ diameter