

Bayonet quick couplings

Couplings with tail



Straight. Brass

Swivel straight.
Brass. RotatableSuction coupling *.
Brass

Couplings with male and female thread



M thread. Brass

F thread. Flat seal.
Brass

DN
10 mm (3/8")
13 mm (1/2")
16 mm (5/8")
19 mm (3/4")
25 mm (1")
32 mm (1.1/4")
38 mm (1.1/2")

R+M Nr.	ⓘ
720 05	45
720 10	45
720 15	45
720 20	45
720 30	51
720 40	62
720 50	68

R+M Nr.	ⓘ
720 104	60
720 204	55
720 304	67
720 404	75

R+M Nr.	ⓘ
724 30	79
724 15	74
724 25	78

⊙
1/4"
3/8"
1/2"
3/4"
1"
1.1/4"
1.1/2"

R+M Nr.	ⓘ
723 05	23
723 10	24
723 20	24
723 30	22
723 40	23
723 50	26
723 60	35

R+M Nr.	ⓘ
722 10	23
722 20	23
722 30	23
722 40	23
723 00	28
723 01	30

* Leak proof. Twist on sleeve locks in place

Spare washer



Flat seal. For F thread

R+M Nr.	⊙
725 23	3/8"
725 24	1/2"
725 25	3/4"
725 26	1"
725 27	1.1/4"
725 28	1.1/2"



Gasket

R+M Nr.
725 20


Accessories

100 meshes/cm².
Brass. Strainer
insert. ⊙ 33 mm

R+M Nr.
725 30

Bayonet blank
coupling with
gasket. Brass

R+M Nr.
725 10

3-way distributor
3/4" F : 3/4" M :
3/4" M. Brass

R+M Nr.
725 05

3-way bayonet
coupling.
Brass

R+M Nr.
725 00

Low pressure quick coupling ST-45

ST-45.
Nickel-plated brass.
Quick Coupling :
3/4" F.
25 bar / 90 °C

R+M Nr.
200 045 210

ST-45.
Nickel-plated brass.
Quick Coupling :
1" F.
25 bar / 90 °C

R+M Nr.
200 045 230

ST-45.
Nickel-plated brass.
Plug nipple with
hose barb
13-19 mm.
25 bar / 90 °C

R+M Nr.
010 000 455

ST-45.
Nickel-plated brass.
Plug nipple with
hose barb
19-25 mm.
25 bar / 90 °C

R+M Nr.
010 000 456

KTW approved bayonet quick couplings are available on request!

Symbols ⊙ thread ⓘ height DN nominal diameter ⊘ diameter