

Suttner high pressure spray guns

ST-601 linear standard



Standard.

Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
200 601 600	1/4" F	3/8" F

ST-601 linear freeze stop



limited stock

Freeze stop version.

Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
200 601 601	1/4" F	3/8" F

ST-601 linear standard



limited stock

Standard.

Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
200 601 661	1/4" F	M22x1.5 M swivel

ST-1500 freeze stop



Professional gun. Freeze stop version.

Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 580	1/4" F	3/8" F

ST-1500 freeze stop



Professional gun. Freeze stop version.

Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 581	1/4" F	3/8" F swivel

ST-1500 weep



Professional gun. Weep version.

Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 620	1/4" F	3/8" F

ST-1500 without trigger



Professional gun without trigger.

Max. 275 bar / 45 l/min / 150 °C

ST-1500C



Professional gun. Ceramic ball, chemical resistant valve and acid and alkali resistant PEEK sealing seat.

FKM seals.

Stainless steel in- and outlet.

By using PEEK as sealing seat material, the gun is also particularly suitable for pre-spray and pre-wash applications in vehicle washing

Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 750	1/4" F	3/8" F

R+M Nr.		
201 500 572	1/4" F	3/8" F

ST-300 swivel




1/4" F : 3/8" F. ST-1500

Repair kit ST-300

R+M Nr.
200 300 050

R+M Nr.
200 300 100

ST-301 swivel



1/4" F : 3/8" F. ST-2300

Repair kit ST-301

R+M Nr.
200 301 050

R+M Nr.
200 300 100

Valves



ST-601



ST-2300. Freeze stop



ST-2300. Weep



ST-1500. Freeze stop



ST-1500. Weep



ST-1500C. ST-601 Resistant to chemicals

R+M Nr.
202 000 044

R+M Nr.
202 300 457

R+M Nr.
202 300 491

R+M Nr.
202 000 101

R+M Nr.
202 000 045

R+M Nr.
202 000 054