

Suttner high pressure quick couplings ST-45-250 KW

Couplings and plug ST-45-250 KW



Coupling : M.
Stainless steel.
Max. 250 bar / 150 °C



Coupling : F.
Stainless steel.
Max. 250 bar / 150 °C



Coupling : F.
Stainless steel.
Max. 250 bar / 150 °C



Plug : F.
Hardened stainless steel.
Max. 250 bar / 150 °C

⊙	DN
1/4"	10
3/8"	10
1/2"	10
M22	10

R+M Nr.	⌈
200 045 595	49 mm

R+M Nr.	⌈
200 045 570	41 mm
200 045 560	41 mm
200 045 550	41 mm
200 045 575	41 mm

R+M Nr.	⌈
200 045 565	43 mm
200 045 555	43 mm

R+M Nr.	⌈
040 005 482	38 mm



Plug : M.
Stainless steel.
Max. 250 bar / 150 °C



Plug : M.
Hardened stainless steel.
Max. 250 bar / 150 °C



Coupling : F.
Nickel-plated brass.
Max. 250 bar / 150 °C



Coupling : F.
Nickel-plated brass.
Max. 250 bar / 150 °C

⊙	DN
1/4"	10
3/8"	10
1/2"	10

R+M Nr.	⌈
557 206	44 mm

R+M Nr.	⌈
040 005 669	42 mm

R+M Nr.	⌈
200 045 510	41 mm

R+M Nr.	⌈
200 045 505	43 mm




Plug : F.
Zinc-plated steel.
Max. 250 bar / 150 °C



Plug : F.
Stainless steel.
Max. 250 bar / 150 °C



Plug : F.
Hardened stainless steel.
Max. 250 bar / 150 °C



O-ring large FKM

R+M Nr.	VPE
791 824 100	100

⊙	DN
3/8"	10
1/2"	10

R+M Nr.	⌈
557 204	38 mm


R+M Nr.	⌈
557 209	38 mm
557 29	45 mm

R+M Nr.	⌈
557 209 2	38 mm

R+M Nr.	VPE
792 026 100	100



Plug : F.
Zinc-plated steel + brass.
Max. 250 bar / 150 °C



Coupling : M.
Nickel-plated brass + brass.
Max. 250 bar / 150 °C

⊙	DN
M22	10

R+M Nr.	⌈
557 205	73 mm

R+M Nr.	⌈
557 105	63 mm



Seal kit

R+M Nr.	M
200 045 465	FKM

Symbols ⌈ height DN nominal diameter ⊙ thread VPE packing unit ∅ diameter TYP type M material