



ARS 178 L - BALL-TYPE QUICK COUPLING 12,5 MPA -SST

P/N	Inlet	Type	Weight			
			gr	oz		
26.2500.10	3/8 Bsp F	B	105	3,7	5	✓
26.2500.30	1/2 Bsp F	B	132	4,66	5	✓
26.2500.40	1/2 Bsp M	B	140	4,94	5	✓
26.2530.00	1/4 Bsp F	A	50	1,7	5	✓
26.2530.10	3/8 Bsp F	A	50	1,7	5	
26.2530.30	1/2 Bsp F	A	86	3,03	5	✓
26.2530.40	1/2 Bsp M	A	50	1,7	5	✓

Rated Pressure	125 bar - 12,5 MPa	1825 psi
Permissible Pressure	140 bar - 14 MPa	2025 psi
Rated Flow	50 l/min	13,2 USGpm
Rated Temperature	90 °C	195 °F
Material	Stainless steel	

Pin Ø17,8 mm - Internal hole Ø12 mm



ARS 220 - BALL-TYPE QUICK COUPLING 220 BAR

P/N	Inlet	Type	Weight			
			gr	oz		
26.2030.20	1/4 Bsp F	B	184	6,49	25	
26.2030.25	1/4 Bsp M	B	196	6,91	25	
26.2030.00	3/8 Bsp F	B	173	6,12	25	✓
26.2030.80	M 22 F	B	156	5,5	25	✓
26.2040.61R	1/4 Bsp F	A	69	2,43	25	✓
26.2045.61R	1/4 Bsp M	A	60	2,12	25	
26.2035.61R	3/8 Bsp F	A	58	2,05	25	✓

Rated Pressure	220 bar - 22 MPa	3200 psi
Permissible Pressure	250 bar - 25 MPa	3650 psi
Rated Flow	50 l/min	13,2 USGpm
Rated Temperature	90 °C	195 °F

Pin Ø19,9 mm - Internal hole Ø12 mm- Compatible with ARS350



ARS 178 - BALL-TYPE QUICK COUPLING 25 MPA -SST

P/N	Inlet	Type	Weight			
			gr	oz		
26.2500.10	3/8 Bsp F	B	105	3,7	5	✓
26.2500.30	1/2 Bsp F	B	132	4,66	5	✓
26.2500.40	1/2 Bsp M	B	140	4,94	5	✓
26.2520.00R	1/4 Bsp F	A	47	1,66	5	✓
26.2520.10R	3/8 Bsp F	A	50	1,7	5	✓
26.2520.30R	1/2 Bsp F	A	87	3,07	5	✓
26.2520.40R	1/2 Bsp M	A	60	2,12	5	✓

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	50 l/min	13,2 USGpm
Rated Temperature	90 °C	195 °F
Material	Stainless steel	

Pin in hardened stainless steel Ø17,8 mm - Internal hole Ø12 mm

