Accessories quick connect spray nozzles

Coupling 1/4" F NPT

R+M Nr.
550 001 40

Nipple 1/4" M NPT

R+M Nr.
550 011 40

Nozzle holder for quick connect spray nozzles. Suitable for 1/4" lances. Without accessories

R+M Nr.
020 002 510

Quick connect nozzle set by Suttner

» Consisting of:
colored plastic holder inclusive:
1 x Low pressure nozzle. Brass,
1 x Flushing nozzle. Stainless steel,
1 x Chiseling nozzle. Stainless steel,
1 x Blasting nozzle. Stainless steel
» High strength plastic. Highly impact resistant
» Stainless steel nozzles: long lifetime and excellently thermal and chemical stability, resistant to mineral acids and alkaline solutions.
» Connection ST-245 coupling, G 1/4" F, **R+M Nr. 200 245 500**
» Suitable for applications requiring a frequent and quick change of the spraying angle
» Max. 350 bar

D	R+M Nr.	G
030	125 852 030	ST-245
035	125 852 035	ST-245
040	125 852 040	ST-245
045	125 852 045	ST-245

Colour coding of Suttner nozzle set holder according to nozzle size



030 yellow | **035** purple | **040** brown | **045** green

65°	40°	15°	0°
Low pressure nozzle. Brass. Designed for prespraying detergents on all kinds of surfaces. Low pressure rinsing.	**Flushing nozzle.** Stainless steel. Best suited for flushing dirt, mud and grime.	**Chiseling nozzle.** Stainless steel. The spray should be directed at a 45° angle to the surface and used like a scraper to remove paint, grease and dirt.	**Blasting nozzle.** Stainless steel. Delivers a very concentrated stream of water. **Care should be used to avoid gouging wood or damaging fragile surfaces.**