

LANCE ML - ROUND GRIP - STAINLESS STEEL TUBE

P/N	Inlet	Length		Outlet	Weight			
		mm	in.		gr	oz		
40.6205.00	1/4 Bsp M	1200	47,2	1/4 Npt F	872	30,76	25	✓
40.6205.05	1/4 Npt M	1200	47,2	1/4 Npt F	872	30,76	25	
40.6505.00	1/4 Bsp M	1500	59	1/4 Npt F	1080	38,09	10	✓
40.6705.00	1/4 Bsp M	1700	66,9	1/4 Npt F	1300	45,8	10	
40.7005.00	1/4 Bsp M	2000	78,7	1/4 Npt F	1295	45,68	10	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Lances with tip protector and nozzle holder.



LANCE PFL - MOULDED GRIP - ZINC-PLATED TUBE

P/N	Length		Type	Outlet	Weight			
	mm	in.			gr	oz		
40.7500.00	500	19,8	Bent	1/4 Npt F	390	13,76	25	✓
40.7502.00	500	19,8	Straight	1/4 Npt F	398	14,04	25	
40.7700.00	700	27,5	Bent	1/4 Npt F	488	17,21	25	✓
40.7700.50	700	27,5	Bent	1/8 Npt F	488	17,21	25	
40.7900.00	900	35,4	Bent	1/4 Npt F	599	21,13	25	✓
40.7900.50	900	35,4	Bent	1/8 Npt F	599	21,13	25	
40.8200.00	1200	47,2	Bent	1/4 Npt F	853	30,09	25	✓
40.8500.00	1500	59	Bent	1/4 Npt F	1024	36,12	10	✓
40.8700.00	1700	66,9	Bent	1/4 Npt F	1116	39,36	10	✓
40.9000.00	2000	78,7	Bent	1/4 Npt F	1319	46,52	10	✓

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F
Inlet		1/4 Bsp M

Lances with tip protector and nozzle holder.
Lances with outlet 1/8Npt F available on request.



LANCE PFL - MOULDED GRIP - SST TUBE

P/N	Length		Type	Outlet	Weight			
	mm	in.			gr	oz		
40.7518.00	500	19,8	Straight	1/4 Npt F	346	12,2	25	✓
40.7722.00	700	27,5	Bent	1/4 Npt F	434	15,31	25	✓
40.9025.00	900	35,4	Bent	1/4 Npt F	507	17,88	25	
40.8216.00	1200	47,2	Bent	1/4 Npt F	738	26,03	10	✓

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F
Inlet		1/4 Bsp M
Tube type		Stainl. steel

Lances with tip protector and nozzle holder.
Lances with outlet 1/8Npt F available on request.

