



LD9 - WITH S3 VENTED GRIP

P/N	Length		Tube type	Outlet	Weight			
	mm	in.			gr	oz		
41.0905.00	690	27	1/4 Sst.	1/4 Npt F	934	32,94	10	✓
41.0805.00	890	35	1/4 z.pl.	1/4 Npt F	1300	45,85	10	✓
41.0806.00	890	35	1/4 Sst.	1/4 Npt F	1183	41,73	10	✓
41.0800.00	1090	43	1/4 z.pl.	1/4 Npt F	1528	53,89	10	✓
41.0900.00	1090	43	1/4 Sst.	1/4 Npt F	1347	47,51	10	✓
41.0850.00	1090	43	1/8 Sst.	1/4 Npt F	1208	42,61	10	
41.0902.00	1600	63	1/4 Sst.	1/4 Npt F	1851	65,29	3	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F
Inlet		1/4 Bsp M



LD7/3 - WITH S3 VENTED GRIP

P/N	Length		Tube type	Outlet	Weight			
	mm	in.			gr	oz		
41.0600.00	1070	42,1	1/8 Sst.	1/4 Npt F	1106	39	10	
41.0630.00	890	35	1/4 z.pl.	1/4 Npt F	1223	43,14	10	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F
Hand Grip		S3
Inlet		1/4 Bsp M



LD7 - WITH R5 ROUND GRIP

P/N	Inlet	Length		Tube type	Weight			
		mm	in.		gr	oz		
41.0682.00	1/4 Bsp M	1050	41,3	1/4 z.pl. × 1/8 Sst.	1060	37,4	10	✓
41.0682.05	1/4 Npt M	1050	41,3	1/4 z.pl. × 1/8 Sst.	1060	37,4	20	
41.0684.00	1/4 Bsp M	850	33,4	1/4 z.pl. × 1/8 Sst.	948	33,44	10	✓
41.0684.05	1/4 Npt M	850	33,4	1/4 z.pl. × 1/8 Sst.	948	33,44	20	
41.0672.00	1/4 Bsp M	1050	41,3	1/4 × 1/8 Sst.	1037	36,58	10	✓
41.0672.05	1/4 Npt M	1050	41,3	1/4 × 1/8 Sst.	1037	36,58	20	
41.0674.00	1/4 Bsp M	850	33,4	1/4 × 1/8 Sst.	922	32,52	10	✓
41.0674.05	1/4 Npt M	850	33,4	1/4 × 1/8 Sst.	922	32,52	20	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F
Hand Grip		R5
Outlet		1/4 Npt F



LD - WITH VERTICAL VALVE

P/N	Hand Grip	Length		Tube type	Weight			
		mm	in.		gr	oz		
41.0330.00	1-PFL	850	33,4	1/4 z.pl.	1006	35,48	15	✓
41.0340.00	R5	1050	41,3	1/4 z.pl.	1026	36,19	10	
41.0880.00	LD9+S3+knob	1090	43	1/4 z.pl.	1578	55,66	10	✓
41.0881.00	LD9+S3+knob	1090	43	1/4 Sst.	1365	48,14	10	✓

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F
Outlet		1/4 Npt F
Inlet		1/4 Bsp M

