

Annovi Reverberi motor pumps

Motor pumps series 198

Repair kits



Pump with regulation valve* and injector. Voltage 400/50 Hz (170 204 20), Voltage 230/50 Hz (170 204 15)

P	☐	U	KW	TYP
120	8	2,800	1.8	HPJ8.12REG
140	11	2,800	3.0	HPJ11.14REG

R+M Nr.
170 204 15
170 204 20

Valves 6 pieces

R+M Nr.
170 286 9
170 286 9

Seal kits for 3 pistons

R+M Nr.
170 279 8
170 279 8

Oil seal kits (5 pieces)

R+M Nr.
170 251 1
170 251 1

Ceramic sockets for 3 pistons

R+M Nr.	KØ	I
170 279 6	15	40
170 279 6	15	40

Motor pumps series 228

Repair kits



Motor pump without regulation valve. Voltage 400/50 Hz

P	☐	U	KW	TYP
200	15	1,450	5.5	HRK15.20H
150	21	1,450	5.5	HRK21.15H

R+M Nr.
170 208 62
170 208 67

Valves 6 pieces

R+M Nr.
170 286 4
170 286 4

Seal kits for 3 pistons

R+M Nr.
170 185 7
170 188 8

Oil seal kits (7 pieces)

R+M Nr.
170 185 5
170 185 5

Ceramic sockets for 3 pistons

R+M Nr.	KØ	I
170 275 7	18	40
170 275 9	22	40

* Setting up of a regulation valve: page 68

Symbols P pressure ☐ flow U revolutions KW kilowatt TYP type KØ piston diameter I height

Annovi Reverberi motor pumps

Motor pump combinations



400 V. All models are equipped with a regulation valve*, delayed total stop control, pressure gauge, 5 m electric cable and an on-off switch. $\odot$ 1/2" M $\odot$ 3/8" M.
Max. 30 °C

P	U	KW	TYP
150	15	1,450	4 MTP HXM 15.15
150	21	1,450	5.5 MTP HRK 21.15
200	15	1,450	5.5 MTP HRK 15.20
150	26	1,450	7.5 MTP HXW 26.15
150	30	1,450	7.5 MTP HXW 30.15

R+M Nr.
170 208 711
170 257 56
170 238 68
170 260 58
170 260 60

Repair kits



Valves 6 pieces



Seal kits for 3 pistons



Oil seal kits



Ceramic socket for 3 pistons



Unloader Gymatic 3/B



400 V. All versions with regulation valve*, delayed total stop control, flow switch ST-7, pressure gauge, electric cable 5 m and on/off switch.


$\odot$ 1/2" M incl. quick coupling "Universal" plug $\odot$ 3/8" M.
Max. 30 °C

P	U	KW	TYP
150	15	1,450	4 MTP XM 15.15
170	14	1,450	4 MTP XM 17.14

R+M Nr.
170 294 33
170 294 32



Valves 6 pieces



Seal kits for 3 pistons



Oil seal kits



Ceramic socket for 3 pistons



Unloader Gymatic 3/B



400 V. All models are equipped with a regulation valve*, delayed total stop control, pressure gauge, 5 m electric cable and an on-off switch. $\odot$ 1/2" F $\odot$ 3/8" M.
Max. 85 °C at min. 2 bar inlet pressure

P	U	KW	TYP
150	15	1,450	4 MTP HRWH 15.15
150	21	1,450	5,5 MTP HRWH 21.15

R+M Nr.
170 269 18
170 269 11



Valves 6 pieces



Seal kits for 3 pistons



Oil seal kits (7 pieces)



Ceramic socket for 3 pistons



Unloader Gymatic 3/B

P	U	KW	TYP
150	15	1,450	4 MTP HRWH 15.15
150	21	1,450	5,5 MTP HRWH 21.15

R+M Nr.
170 269 18
170 269 11

R+M Nr.
170 423 28
170 423 28

R+M Nr.
170 423 29
170 465 14

R+M Nr.
170 185 5
170 185 5

R+M Nr.	KØ	I
170 250 0	18	40
170 252 6	22	45

R+M Nr.
170 223 08
170 223 08

* Setting up of a regulation valve: page 68