



SW65 - LARGE FLOW BALL SWIVEL

P/N	Inlet	Outlet	Weight			
			gr	oz		
30.6480.00	1/2 Bsp F	1/2 Bsp M	120	4,23	5	✓
Rated Pressure			24 bar - 2,4 MPa		350 psi	
Rated Flow			100 l/min		26,5 USGpm	
Rated Temperature			100 °C		212 °F	
Max. working temperature			90 °C		194 °F	
Max. RPM					30 giri/min	
Material					Brass	



SW5- LARGE FLOW SWIVEL

P/N	Inlet	Outlet	Mat.	Weight			
				gr	oz		
26.1070.00	1/2 Bsp M	1/2 Bsp F	Sst Ai 303	102	3,6	10	✓
26.1076.00	1/2 Bsp M	1/2 Bsp F	Sst Ai 316L	102	3,6	5	✓
26.1080.00	1/2 Bsp M	1/2 Bsp F	Brass	117	4,13	10	✓
Rated Pressure		200 bar - 20 MPa		2900 psi			
Permissible Pressure		220 bar - 22 MPa		3200 psi			
Rated Flow		160 l/min		42 USGpm			
Rated Temperature		90 °C		194 °F			
Max. temperature for short		160 °C		320 °F			



LR - LIGHT DUTY SWIVEL

P/N	Inlet	Outlet	Weight			
			gr	oz		
26.1000.00	3/8 Bsp M	3/8 Bsp F	75	2,65	10	✓
26.1000.05	3/8 Bsp M	1/4 Bsp F	82	2,89	10	✓
26.1000.10	3/8 Npt M	3/8 Npt F	76	2,6	10	✓
Rated Pressure			220 bar - 22 MPa		3200 psi	
Permissible Pressure			250 bar - 25 MPa		3650 psi	
Rated Flow			30 l/min		8 USGpm	
Rated Temperature			90 °C		195 °F	
Max. working temperature			60 °C		140 °F	
Material					Brass	



MR-O - BRASS SWIVEL

P/N	Inlet	Outlet	Weight			
			gr	oz		
26.1040.00	1/4 Bspt M taper 60°	1/4 Bsp F	173	6,1	10	✓
26.1050.00	3/8Bspt M taper 60°	3/8 Bsp F	173	6,1	10	✓
26.1055.00	1/2 Bsp M	1/2 Bsp F	216	7,62	10	✓
Rated Pressure			250 bar - 25 MPa		3650 psi	
Permissible Pressure			280 bar - 28 MPa		4050 psi	
Rated Flow			40 l/min		10,5 USGpm	
Rated Temperature			160 °C		320 °F	
Max. working temperature			90 °C		194 °F	
Material					Brass	

