


AR4 - COUPLER M22 +HEXAGONAL JOINT - BSP

P/N	Type	Inlet	Weight				
			gr	oz			
26.0220.00	B 2 pcs	1/4 Bsp F	80	2,82	25	✓	
26.0225.31R	A	1/4 Bsp F	70	2,4	25	✓	
26.0199.31R	A1	1/4 Bsp M	70	2,4	10	✓	
10.3185.00R	C	Nbr	0,5	0,02	10	✓	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M22x1,5 F with hexagonal joint and external O-ring to prevent unscrewing




AR3 - COUPLER M22 +HEXAGONAL JOINT - BSP

P/N	Type	Inlet	Weight				
			gr	oz			
26.0205.00	B 2 pcs	1/4 Bsp F	74	2,61	25	✓	
26.0199.31R	A	1/4 Bsp M	70	2,4	10	✓	
26.0200.31R	A	1/4 Bsp F	74	2,61	25	✓	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M22x1,5 F with hexagonal joint




AR3/23 - COUPLER M22 + HEXAGONAL JOINT - BSP

P/N	Type	Inlet	Weight				
			gr	oz			
26.0210.00	B 2 pcs	1/4 Bsp F	108	3,81	5	✓	
26.0199.31R	A	1/4 Bsp M	70	2,4	10	✓	
26.0200.31R	A	1/4 Bsp F	70	2,4	25	✓	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M22x1,5 F with hexagonal joint



ARG - REVOLVING COUPLER TYPE "B" M22 - 1 O-RING

P/N	Inlet	Type	Weight				
			gr	oz			
26.0900.00	1/4 Bsp M	B 2 pcs	133	4,69	15	✓	
26.0910.00	A M22	B 3 pcs	192	6,77	15	✓	

Rated Pressure	250 bar - 25 MPa	3650 psi
Permissible Pressure	280 bar - 28 MPa	4050 psi
Rated Flow	40 l/min	10,5 USGpm
Rated Temperature	160 °C	320 °F

Pin Ø14 mm - M22x1,5 F - revolving even under pressure - suitable for connecting spray gun and lance

