

URF 180 - ROTATING HEAD

P/N	Inlet	Outlet	Weight			
			gr	oz		
25.1130.00	1/4 Npt M	2 x 1/8 Bsp F	170	6	5	✓
Rated Pressure	250 bar - 25 MPa		3650 psi			
Permissible Pressure	280 bar - 28 MPa		4050 psi			
Rated Flow	30 l/min		8 USGpm			
Rated Temperature	0-80 °C		32-175 °F			



URF 400 - ROTATING HEAD

P/N	Inlet	Outlet	Weight			
			gr	oz		
25.1170.00	1/2 Bsp F	2 x 1/4 Bsp F	440	15,52	1	✓
Rated Pressure	350 bar - 35 MPa		5100 psi			
Permissible Pressure	390 bar - 39 MPa		5650 psi			
Rated Flow	80 l/min		21 USGpm			
Rated Temperature	0-80 °C		32-175 °F			



GR 38 - ROTATING TANK CLEANER

P/N	Inlet	Outlet	Weight			
			gr	oz		
26.1400.00	3/8 Bsp M	2 x M12 F	637	22,47	1	✓
Rated Pressure	350 bar - 35 MPa		5100 psi			
Permissible Pressure	390 bar - 39 MPa		5650 psi			
Rated Flow	40 l/min		10,5 USGpm			
Rated Temperature	120 °C		250 °F			
Max. working temperature	0-90 °C		32-195 °F			



GR38/200-400 - ROTATING HEAD

P/N	Width		Inlet	Outlet	Weight			
	mm	in			gr	oz		
26.1420.00	210	8,26	3/8 Bsp M	2 x 1/8 Npt F	759	26,77	1	✓
26.1440.00	400	15,75	3/8 Bsp M	2 x 1/8 Npt F	852	30,05	1	✓
Rated Pressure	350 bar - 35 MPa		5100 psi					
Permissible Pressure	390 bar - 39 MPa		5650 psi					
Rated Flow	40 l/min		10,5 USGpm					
Rated Temperature	120 °C		250 °F					
Max. working temperature	0-90 °C		32-195 °F					



GR58/400 - ROTATING HEAD

P/N	Width		Inlet	Outlet	Weight			
	mm	in			gr	oz		
26.1460.00	400	15,75	1/2 Bsp F	2 x 1/8 Npt F	900	31,75	1	
Rated Pressure	500 bar - 50 MPa		7250 psi					
Permissible Pressure	560 bar - 56 MPa		8100 psi					
Rated Flow	40 l/min		10,5 USGpm					
Rated Temperature	120 °C		250 °F					
Max. working temperature	0-90 °C		32-195 °F					

