

Suttner rotating nozzles for sewer cleaning ST-49.1

Rotating nozzles ST-49.1 without centric hole



1/8" F. ⌀ 19 mm. Max. 250 bar



1/4" F. ⌀ 19 mm. Max. 250 bar



3/8" F. ⌀ 24 mm. Max. 250 bar

D
04
045
05
055
06
07
08
090
10
12
15
20

R+M Nr.
200 049 825
200 049 830
200 049 835
200 049 840
200 049 845
200 049 850

R+M Nr.
200 049 794
200 049 795
200 049 800
200 049 805
200 049 810
200 049 815
200 049 820

R+M Nr.
651 61 *

R+M Nr.
651 62 **

R+M Nr.
200 049 860
200 049 870
200 049 880
200 049 890
200 049 891
200 049 892
200 049 893
200 049 894
200 049 895

ST-49.1 with centric hole



3/8" F. ⌀ 24 mm. Max. 250 bar

D
10
12
15
18

R+M Nr.
200 049 896
200 049 897
200 049 898
200 049 899

Suttner mini rotating nozzles for sewer cleaning ST-49.3

1/8" F. Nozzle with thrust. ⌀ 12 mm.
Ideal for cleaning or flushing out pipes as well as adjoining lateral pipes at any angle. Small pump capacities required, only. 2 rotating radial jets (90°) to the pipe wall for best cleaning results. 2 rotating rear jets (45°) for forward thrust and flushing away of the waste material. Suitable for pipes from 14 - 50 mm. Hardened stainless steel. Max. 500 bar




R+M Nr.	D
200 049 950	05
200 049 970	07

- Applications:**
- » Cleaning of deposits
 - » Cleaning of grease, fat and organic deposits
 - » To clean heat exchangers




Functional principle



* Two side jets
** Additional two side jets and three front jets. Reduced thrust, only.

Functional principle



Symbols D nozzle ⌀ diameter