

FYO - BRASS Y-STRAINER

P/N	Couplings	Length		Height		Weight			
		mm	in.	mm	in.	gr	oz		
28.0160.00R	3/8 Bsp F	56	2,2	39,5	1,55	139	4,9	5	✓
28.0162.00R	1/2 Bsp F	59	2,3	40	1,57	158	5,57	5	✓
28.0164.00R	3/4 Bsp F	70	2,75	48,5	1,91	247	8,71	5	✓
28.0162.50R	1/2 Npt F	59	2,3	40	1,57	154	5,43	5	✓

Rated Pressure 12 bar - 1,2 MPa 175 psi
 Rated Temperature 90 °C 195 °F
 Material Brass + Sst net
 Filtration parameter 45 mesh 400 µm



SUCTION NET STRAINER WITH HOSE BARB

P/N	Rated Flow		Hose barb		Weight			
	l/min	USGpm	mm	in.	gr	oz		
15.0000.02R	30	8	20	0,78	32	1,13	5	✓
15.0000.01R	55	14,5	25	1,0	36	1,27	5	✓

Rated Pressure 6 bar - 0,6 MPa 85 psi
 Rated Temperature 40 °C 104 °F
 Material PPL + FG
 Filtration parameter 30 mesh 600 µm



SUCTION NET STRAINER WITH THREADED BARB

P/N	Rated Flow		Outlet	Weight			
	l/min	USGpm		gr	oz		
15.0000.05R	55	14,5	1" Bsp F	40	1,41	5	

Rated Pressure 6 bar - 0,6 MPa 85 psi
 Rated Temperature 40 °C 104 °F
 Material PPL + FG
 Filtration parameter 30 mesh 600 µm



SUCTION STRAINER WITH HOSE BARB AND CHECK VALVE

P/N	Hose barb		Type	Weight			
	mm	in.		gr	oz		
28.0060.00R	19	0,75	Check valve	40	1,41	10	✓
28.0062.00R	19	0,75	-	24	0,85	10	

Without check valve

Rated Pressure 0,6 bar - 0,06 MPa 9 psi
 Rated Temperature 40 °C 104 °F
 Material PPL

