

Cartridge filter



Plastic cleanable. Reinforced version.
Max. 40 °C

R+M Nr.	★	fi	microns	I
734 293 00	■ ■	5"	60	125
734 293 02	■ ■ ■ ■	9.3/4"	60	250
734 293 03	■ ■ ■ ■	9.3/4"	120	250



Plastic cleanable.
Max. 40 °C

R+M Nr.	★	fi	microns	I
734 55	■	5"	60	128
734 54	■	5"	150	128
734 75	■ ■ ■	9.3/4"	60	250
734 74	■ ■ ■	9.3/4"	150	250



Cotton.
Max. 40 °C

R+M Nr.	★	fi	microns	I
734 57	■	5"	5	128
734 56	■	5"	20	128
734 77	■ ■ ■ ■	9.3/4"	5	250
734 76	■ ■ ■ ■	9.3/4"	20	250



Iron remove filter

R+M Nr.	★	fi	←	I
734 709 060	■ ■ ■ ■	9.3/4"	0.85	250



Water softener. Polyphosphate

R+M Nr.	★	fi	I
734 58	■ ■	5"	125
734 820 035	■	20"	510

The filters
734 58, 734 820 035 and
734 709 060
are not suitable for the
water supply of pumps.



Polypropylene. Max. 40 °C

R+M Nr.	★	fi	microns	I
734 720 006	■	20"	5	510
734 720 050	■	20"	50	510



Stainless steel. Max. 120 °C

R+M Nr.	★	fi	microns	I
734 709 050	■ ■ ■ ■	9.3/4"	50	250

The higher the number of microns the more coarsely meshed are the meshes: 500 microns = coarse . 50 microns = fine

Symbols ★ marking fi filter ○ thread I height TYP type