


Drosselhohlschraube

mit Schlitzschraube und Kontermutter
Screw for flow regulation with nut and slotted screw
Asta con regolazione a cacciavite e dado di bloccaggio



ITV	Typ	G	H	L1	L2	1	2	NI/min*
304011	A	G1/8	8	25,5	32	14	8	310
304012	A	G1/4	8	28	35	17	10	810
304013	B	G1/8	8	25,5	32	14	8	310
304014	B	G1/4	8	28	35	17	10	810
304015	C	G1/8	8	25,5	32	14	8	310
304016	C	G1/4	12	28	35	17	10	810


* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar
* portata nominale a 6 bar

Körper:	CW614N vernickelt
Body:	CW614N nickel-plated
Corpo:	ottone CW614N nichelato
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +80 °C
Working temperature:	-20 °C up to +80 °C
Temperatura di esercizio:	da -20 °C a +80 °C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Für geölte und ungeölte Druckluft. For lubricated and non-lubricated compressed air. Per aria compressa sia lubrificata che non.	

A = Zuluft / for valves / per valvola B = Abluft / for cylinders / per cilindro C = Beidseitig / bidirectional / bidirezionale

Drosselhohlschraube

mit Rändelkopf und Kontermutter
Screw for flow regulation with nut and regulating spindle
Asta con manopola zigrinata



ITV	Typ	G	H	L1	L2	1	2	NI/min*
304021	A	G1/8	6	32	23,5	14	9	340
304022	A	G1/4	9,5	37	27	17	11	580
304023	B	G1/8	6	32	23,5	14	9	340
304024	B	G1/4	9,5	37	27	17	11	580
304025	C	G1/8	6	32	23,5	14	9	340
304026	C	G1/4	9,5	37	27	17	11	580

* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar
* portata nominale a 6 bar

Körper:	CW617N
Body:	CW617N
Corpo:	ottone CW617N nichelato
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +80 °C
Working temperature:	-20 °C up to +80 °C
Temperatura di esercizio:	da -20 °C a +80 °C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Für geölte und ungeölte Druckluft. For lubricated and non-lubricated compressed air. Per aria compressa sia lubrificata che non.	

A = Zuluft / for valves / per valvola B = Abluft / for cylinders / per cilindro C = Beidseitig / bidirectional / bidirezionale