


Mini-Kugelhahn 631

konisch
Mini ball valve 631 con.
Valvola a sfera micro maschio conico femmina cilindrica
631




ITV	R	G	H	L	D	E	DN	1	2
63102	R1/8	G1/8	8	35,5	19,5	21,5	5,5	14	-
63103	R1/4	G1/4	11	40,5	19,5	21,5	5,5	14	-
63104	R3/8	G3/8	11,5	44,5	19,5	23	8	18	-
63105	R1/2	G1/2	17	58	25	32	10	22	22
63106	R3/4	Rp3/4	16,5	63	50	33	14	28	30

Betriebstemperatur:	-20 °C bis +80 °C
Operating temperature:	-20 °C to +80 °C
Temperatura di esercizio:	da -20 °C a +80 °C
Betriebsdruck:	20 bar
Inlet pressure:	20 bar
Pressione di esercizio:	20 bar
Körper/Kugel:	Messing verchromt
Body/ball:	brass chrome-plated
Corpo/sfera:	ottone cromato
Griff:	PA66
Handle:	PA66
Leva:	PA66
O-Ring:	NBR 70
O-ring:	NBR 70
O-Ring:	NBR 70
Gewinde:	DIN EN ISO 228/ DIN EN ISO 10226
Thread:	DIN EN ISO 228/ DIN EN ISO 10226
Filettatura:	DIN EN ISO 228/ DIN EN ISO 10226
Einsatzgebiete:	Luft-, Wasser-, Ölkreisläufe, Einsatz auch im mittleren bis niedrigen Vakuum möglich.
Applications:	Air, Water and Oil dynamics circuits, use also in medium to low vacuum.
Campo di applicazione:	Aria, acqua e circuiti oleodinamici; e' possibile l'utilizzo per medio/ basso vuoto pneumatico.

Mini-Kugelhahn 641

zylindrisch
Mini ball valve 641 parallel
Valvola a sfera micro 641



ITV	G1	G2	H1	H2	L	D	E	DN	1
64101	G1/8	G1/8	7	8	34,5	19,5	21,5	5,5	14
64102	G1/4	G1/8	8	8	35,0	19,5	21,5	5,5	14
64103	G1/4	G1/4	8	11	37,5	19,5	21,5	5,5	14
64104	G3/8	G1/4	9	11	38,5	19	21,5	5,5	14

Betriebstemperatur:	-20 °C bis +80 °C
Operating temperature:	-20 °C to +80 °C
Temperatura di esercizio:	da -20 °C a +80 °C
Betriebsdruck:	20 bar
Inlet pressure:	20 bar
Pressione di esercizio:	20 bar
Körper/Kugel:	Messing verchromt
Body/ball:	brass chrome-plated
Corpo/sfera:	ottone cromato
Griff:	PA66
Handle:	PA66
Leva:	PA66
O-Ring:	NBR 70
O-ring:	NBR 70
O-Ring:	NBR 70
Gewinde:	DIN EN ISO 228
Thread:	DIN EN ISO 228
Filettatura:	DIN EN ISO 228
Einsatzgebiete:	Luft-, Wasser-, Ölkreisläufe, Einsatz auch im mittleren bis niedrigen Vakuum möglich.
Applications:	Air, Water and Oil dynamics circuits, use also in medium to low vacuum.
Campo di applicazione:	Aria, acqua e circuiti oleodinamici; e' possibile l'utilizzo per medio/ basso vuoto pneumatico.