


Rückschlagventil IG-AG

Non-return valve male-female
Valvola di non ritorno M.F.




ITV	G	H	L	↷	NI/min*
305101	G1/8	6	53	14	920
305103	G1/4	9	66	19	1600
305105	G1/2	12	81	27	3500

* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar
* portata nominale a 6 bar

Körper:	CW614N vernickelt
Body:	CW614N nickel-plated
Corpo:	ottone CW614N nichelato
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +80 °C
Working temperature:	-20 °C up to +80 °C
Temperatura di esercizio:	da -20 °C a +80 °C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Für geölte und ungeölte Druckluft.	
For lubricated and non-lubricated compressed air.	
Per aria compressa sia lubrificata che non.	

Drosselrückschlagventil

Kunststoff-Steckanschluss
Acetal Line Flow Regulator
Regolatore di flusso in linea con corpo in resina acetica



ITV	ØD	ØD1	L1	L2	L3	↷	NI/min*
340404	4	3,2	35	36	13	11	140
340606	6	3,2	45	45	16	14	260
340808	8	3,2	46	46	16	14	330

Beidseitig drosselbar bidirectional throttling bidirezionale

340414	4	3,2	35	36	13	11	140
340616	6	3,2	45	45	16	14	260
340818	8	3,2	46	46	16	14	360

* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar
* portata nominale a 6 bar

Körper:	Kunststoff
Body:	Plastics
Corpo:	resina acetica
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +70 °C
Working temperature:	-20 °C up to +70 °C
Temperatura di esercizio:	da -20 °C a +70 °C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Für geölte und ungeölte Druckluft.	
For lubricated and non-lubricated compressed air.	
Per aria compressa sia lubrificata che non.	