


SFEX

Schalldämpfer - Edelstahl
Silencer - INOX
Silenziatore in Acciaio




ITV	G	H1	H2	L	
303168	M5	4	3	8	8
303162	G1/8	6	4	16	13
303163	G1/4	9	4	19	16
303164	G3/8	9	4	21	19
303165	G1/2	10	4	22	24
303166	G3/4	10	4	27	30
303167	G1	15	4	29	36

Material:	Edelstahl AISI 316L
Material:	Inox AISI 316L
Materiale:	Inox AISI 316L
Filterfeinheit:	70 µ
Filter mesh:	70 µ
Elemento filtrante:	70 µ
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Betriebstemperatur:	-20 °C bis +300 °C
Working temperature:	-20 °C up to +300 °C
Temperatura di esercizio:	da -20 °C a +300 °C
zyl. Gewinde:	DIN EN ISO 228
cyl. threads:	DIN EN ISO 228
Filettatura:	DIN EN ISO 228
metr. Gewinde:	DIN EN ISO 262
metr. threads:	DIN EN ISO 262
Filettatura metrica:	DIN EN ISO 262

SEP

Schalldämpfer
Silencer
Silenziatore con pastiglia in sinterizzato



ITV	G	ØB	H1	H2	L	
303038	M5	5	4	2,5	8	8
303032	G1/8	9	6	4	12	13
303033	G1/4	11	8	4	16	16
303034	G3/8	17	9	4	18	19
303035	G1/2	20,5	11	4	19	24
303036	G3/4	28	13	4	24	30
303037	G1	34	15	4	27	36
303039	IG G1/8	11	6	4	13	13

Körper:	Messing
Body:	brass
Corpo:	ottone
Filter:	Sinterbronze
Filter:	sintered bronze
Filtro:	bronzo sferico sinterizzato
Filterfeinheit:	120 µ
Filter mesh:	120 µ
Elemento filtrante:	120 µ
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Betriebstemperatur:	-20 °C bis +150 °C
Working temperature:	-20 °C up to +150 °C
Temperatura di esercizio:	da -20 °C a +150 °C
zyl. Gewinde:	DIN EN ISO 228
cyl. threads:	DIN EN ISO 228
Filettatura:	DIN EN ISO 228
metr. Gewinde:	DIN EN ISO 262
metr. threads:	DIN EN ISO 262
Filettatura metrica:	DIN EN ISO 262