

Claw Couplings and Spray Nozzles

made of Brass for Water

MODY-Safety-Screwing-Claw Couplings with hose barb

Hose connection	L	B	L1	Passage		Weight	Type No.
Hose i.D. 13	77	53.5	42	10	5	190	GSSG 13
Hose i.D. 19	82	53.5	42	16.5	5	215	GSSG 19
Hose i.D. 25	86	53.5	42	20	5	270	GSSG 25

For hose clips type HS (☹ page 387), type ZOS (☹ page 386), or crimping ferrules type LPH (☹ page 389)

Thread types on request (GSSGA 34 in stock)



Original Rubber Ring with support ring for MODY-Safety-Screwing-Claw Couplings made of brass

Resistance	L	D	D1	Material	Temp.°C	Media	Colour	Shore A	Weight	Type No.
Water	7	33.5	21.5	NBR/ Brass	up to +95	Water	black	65°	6	GSGOR-Set



Classic WaterProfi Spray Nozzles made of brass – conical sealing brass to brass (PN 10 bar)

Hose connection	L	Ø Nozzle bore	Weight	Type No.
Hose i.D. 13	100	5	115	SDT 13
Hose i.D. 19	112	6.5	245	SDT 19
Hose i.D. 25	125	7	370	SDT 25



Connection	L	Ø Nozzle bore	Weight	Type No.
Claw Coupling	98	5	220	SDK 12
Claw Coupling	113	6.5	310	SDK 34
Claw Coupling	121	7	410	SDK 10



System-Adapter Claw Coupling - Quick Connect Coupling

Connection	L	B	Weight	Type No.
WaterProfi Claw Coupling - Coupling WPN DN 9	73	54.2	254	WPNK-WPA
WaterProfi Claw Coupling - Plug WPN DN 9	59.5	54.2	160	WPNS-WPA

