

Claw Couplings

US-Version with Bore for Safety-Clips

- Robust claw couplings made of malleable iron, US-Version, zinc-plated and yellow passivated (free of chrome VI)
- 100 % function check and sight control
- With oil-resistant rubber ring GOOR
- When coupled, can be secured against accidental opening through safety-clips DIN 11024
- US-universal coupling, common used system for compressed air supply in construction and industry

Materials

- Claw, connector: Malleable iron zinc-plated and yellow passivated (free of chrome VI)
- Seals: NBR

Max. Working Pressure	Temperature	Thread	Claw distance	Media	
PN 10 bar	-40°C – +95°C	ISO 228, NPT	41 mm	Air a.o.	10

US-Claw Couplings with hose barb and safety collar

Hose connection	L	B	L1	Passage	Weight	Type No.
Hose i.D. 10	75	62	32	6	162	SKA 11*
Hose i.D. 13	88	62	42	9	182	SKA 13
Hose i.D. 19	105	62	56	14	244	SKA 19
Hose i.D. 25	107	62	59	20	286	SKA 25

For US-hose clamps (© page 254)

*SKA 11 two parts with thread stem made of steel

US-Claw Couplings with female thread

Thread connection	L	SW	B	L1	Passage	Weight	Type No.
G 3/8 f	57	27	62	13.5	15	180	KIA 38 BSP
NPT 3/8 f	57	27	62	13.5	15	187	KIA 38
G 1/2 f	57	27	62	13.5	18	173	KIA 12 BSP
NPT 1/2 f	57	27	62	13.5	18	181	KIA 12
G 3/4 f	57	36	62	15	20	195	KIA 34 BSP
NPT 3/4 f	57	36	62	15	20	201	KIA 34
G 1 f	57	42	62	15	20	208	KIA 10 BSP
NPT 1 f	57	42	62	15	20	218	KIA 10

US-Claw Couplings with male thread

Thread connection	L	SW	B	L1	Passage	Weight	Type No.
G 3/8 m	56	29	62	14	9	200	KAA 38 BSP
NPT 3/8 m	64	29	62	15	9	180	KAA 38
G 1/2 m	56	29	62	14	12	210	KAA 12 BSP
NPT 1/2 m	64	29	62	20	12	190	KAA 12
G 3/4 m	64	34	62	16	17	225	KAA 34 BSP
NPT 3/4 m	70	34	62	20	17	224	KAA 34
G 1 m	68	38	62	18	20	250	KAA 10 BSP
NPT 1 m	72	38	62	23	20	260	KAA 10

US-Claw Couplings with blank end

Version	L	B	Weight	Type No.
without chain	55	62	215	UDM

Original Rubber Ring

Resistance	L	D	D1	Material	Temp.°C	Media	Colour	Shore A		Weight	Type No.
Oil	10.5	34	20	NBR	-40 / +95	Compr. Air	black	50 °	100	6	GOOR

Universal Safety Clips DIN 11024

L	B	D	Material		Weight	Type No.
27	63	3	Steel zinc-plated	50	10	USC-1

Coupling not possible with claw distance of 42 mm

