

MT1E STATIC PRESSURE



Caratteristiche principali

- Pressione da 350 a 190 bar - Solo per applicazioni statiche
- Soluzione conduttiva ad alta pressione per vernici e solventi

Main Features

- Pressure from 350 to 190 bar - Static applications only
- High pressure conductive solution for paints and solvents

Caratteristiche tecniche

• Caratteristiche tecnico-costruttive:

Anima interna in polietilene, rinforzo con una treccia in acciaio ad alta resistenza, ricopertura esterna in poliuretano antiabrasione.

• Temperature di utilizzo:

Da -20°C a +60°C (da -4°F a +140°F).

• Pressioni d'esercizio:

Rapporto di sicurezza 1:4.

Pressione da 350 a 190 bar - Solo per applicazioni statiche.

Technical Features

• Technical-constructive features:

Inner core in polyethylene, reinforcement in high tensile steel braid and exterior covering in antiabrasion polyurethane.

• Working temperature:

from -20°C to +60°C (from -4°F to +140°F).

• Working pressure:

Safety ratio 1:4.

Pressure from 350 to 190 bar - Static applications only.

Scheda tecnica - Data Sheet



CODE	inch	-dash	mm	DN	inch	mm	bar	psi	bar	psi	mm	inch	g/m	lbs/ft	FERRULE CODE
MT120000E	3/16"	-3	4.8	5	0.394	10.0	350	5075	467	6772	30	1.18	126	0.085	BP316R7
MT130000E	1/4"	-4	6.4	6	0.469	11.9	300	4350	400	5800	40	1.57	166	0.112	BP14MT1
MT140000E	5/16"	-5	8.0	8	0.551	14.0	240	3480	320	4640	50	1.97	205	0.138	BP516R7V
MT150000E	3/8"	-6	9.7	10	0.630	16.0	225	3262	300	4350	60	2.36	246	0.165	BP38R7V
MT160000E	1/2"	-8	13.0	12	0.756	19.2	190	2755	254	3683	75	2.95	314	0.211	BP12R7V