


Safety Industrial Quick Connect Couplings

with Sleeve Lock Mechanism and Plug Coding - single shut-off **Series ESIK**

DN 7.8

Plug Profile (original size)



Plugs with male thread (thread coated) and plug coding

Thread connection	L	SW	L1	L2	Weight	Type No.
R 1/4 m	39	17	11	23	26	ESIK 14 NARS
R 3/8 m	40	17	12	23	28	ESIK 38 NARS
R 1/2 m	43	22	15	23	44	ESIK 12 NARS



Plugs with female thread and plug coding

Thread connection	L	SW	L1	L2	Weight	Type No.
G 1/4 f	35	17	10	23	25	ESIK 14 NIS
G 3/8 f	35	19	10	23	25	ESIK 38 NIS
G 1/2 f	38	24	12	23	41	ESIK 12 NIS



Plugs with hose barb and plug coding

Hose connection	L	D	L1	L2	Weight	Type No.
Hose i.D. 6	60	18.5	35	23	21	ESIK 6 SS
Hose i.D. 8	60	18.5	35	23	23	ESIK 8 SS
Hose i.D. 9	60	18.5	35	23	24	ESIK 9 SS
Hose i.D. 10	60	18.5	35	23	25	ESIK 10 SS
Hose i.D. 13	60	18.5	35	23	28	ESIK 13 SS

For hose clips type ZOS (© page 130), type HS (© page 131) or crimping ferrules type LPH (© page 133)



OptiFlow
by LUDECKE

