FUB

Fuel Hose



Application:

- Suitable for the delivery of unleaded fuels (EN 228:2004) and diesel oils (EN 590:2004) for cars, trucks and tractors.

Notice:

- Suitable for fuels with a contant of methyl-alcohol of max. 10% .



Temperature range: -40°C / +100°C, Fuel: -30°C / +70°C.

Safety factor: 3,3 : 1

Tube: NBR, black, smooth, ozone and oil resistant.

Insert: Textile spiral construction.

Cover: CR/NBR, black, smooth, ozone and oil resistant.

Marking: Continuous coloured marking, green: "SEMPERIT S FUB KRAFTSTOFF/FUEL DN PN 12BAR"

Article number	Internal-Ø in mm	Internal-Ø in inches	Wall width in mm	External-Ø in mm	Work. pressure (max.) bar	Number of inserts	Bending radius (min.) in mm	Weight approx. kg/m	Coil length (max.) m
68030 0330	3,2	1/8	3,0	9,2	12	2	32	0,08	50
68030 0430	4,0		3,0	10,0	12	2	44	0,08	50
68030 0530	5,0	3/16	3,0	11,0	12	2	50	0,11	50
68030 0531	5,5		3,0	11,5	12	2	55	0,11	50
68030 0630	6,0		3,0	12,0	12	2	60	0,10	50
68030 0631	6,3	1/4	3,0	12,3	12	2	63	0,10	50
68030 0730	7,0		3,0	13,0	12	2	70	0,12	50
68030 0731	7,5		3,0	13,5	12	2	75	0,13	50
68030 0830	8,0	5/16	3,0	14,0	12	2	80	0,13	50
68030 0930	9,0		3,0	15,0	12	2	90	0,14	50
68030 0931	9,5	3/8	3,0	15,5	12	2	95	0,15	50
68030 1030	10,0		3,0	16,0	12	2	100	0,16	50
68030 1235	12,0		3,5	19,0	12	2	120	0,21	50

Please note: General information about our range of products can be found in the appendix to this catalogue. Before using with new or untested media, or before using in applications that are not covered in the product information, written advice must first be obtained from a specialist dealer or a Semperit application engineer. All products must be inspected regularly for operational safety. For safety reasons, hoses must be replaced in the event of damage, especially if the cover is damaged. All products must be stored and maintained according to our storage, care and maintenance instructions, and according to DIN 7716:1982.
We are constantly developing and improving our products for our customers. For the latest product information, please visit our website www.semperflex.com regularly or contact one of our specialist dealers or Semperit application engineers. Contracts are agreed according to our general terms and conditions. Subject to change without notice.

Important notice: This catalogue has been prepared with the greatest care in order to provide you with all the information you need. The information contained herein incorporates the latest state-of-the-art technology, and is the result of trials and tests carried out over many years, or conforms to the resistance requirements of the media listed as set out in ISO TR 7620:2005 (E). The individual conditions of use affect the use of each product. They therefore only ensure the safety that can be expected assuming that the specifications in our written product information, the specifications regarding resistance to chemicals and our cleaning procedures are all complied with. We cannot guarantee this level of safety in the event of improper handling, e. g. squashing, rupturing, stretching or filling with media that are not permitted. Unless specified otherwise, all hoses are manufactured to EN ISO 1307:2006.

Date: 31.08.2007

semperflex® INDUSTRIAL
A MEMBER OF THE SEMPERIT-GROUP